



Overview

Leveringstid	Usually in Stock
--------------	------------------



General

Inkludert utstyr	Installation guide User manual
------------------	-----------------------------------

Physical

Number of rack unit	2U
Farge	Black
Dybde	48,3 cm
Høyde	8,5 cm
Vekt	29,56 kg
Bredde	43,2 cm

Output

Harmonic distortion	Mindre enn 3 %
Output frequency	50/60 Hz +/- 3 Hz user adjustable +/- 0.1 Hz sync to mains
Crest faktor	3:1
Wave type	Sine wave
Bypass type	Built-in static bypass

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0,00...15240,00 m

Batteries & Runtime

Batteritype	Bly-syre batteri
Number of battery filled slots	2
Number of battery free slots	0
Number of battery replacement quantity	2
Tilleggsinformasjon	Replace all batteries in operation together (UPS internal and external batteries) all-at-once
Liquid value	0

Packing Units

Forpakning 1 vekt	32,28 kg
Forpakning 1 høyde	28,6 cm
Forpakning 1 bredde	63 cm
Forpakning 1 lengde	59,4 cm
Antall enheter forpakning 3	6

Contractual warranty

Garanti	2 years repair or replace, optional on-site warranties available, optional extended warranties available
---------	--