



Overview

Presentasjon	For small to medium businesses, Easy UPS 1 Ph On-Line provides essential power protection for unstable power conditions, ensuring consistent and reliable connectivity at the most critical moments.
Leveringstid	Usually in Stock

General

Inkludert utstyr	CD with software User manual USB cable
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS

Physical

Dybde	40 cm
Høyde	23,8 cm
Vekt	7,9 kg
Monteringsmetode	Not rack-mountable
USB compatible	No
Bredde	14,5 cm

Input

Network frequency	40...70 Hz
Plug standard	IEC 60320 C14
Input voltage limits	110...285 V half load 160...280 V fullastet
Inputvolt_other	220 V 240 V
Antall kabler	1
Forsyningsspenning	230 V
Cos phi	0,95

Output

Merkeeffekt i W	2400 W
Maximum configurable power in W	2400 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Output voltage	220 V 240 V
Crest faktor	3:1
UPS type	Double conversion online

Wave type	Sine wave
Nb of power socket outlets	6 IEC 60320 C13 1 IEC 60320 C19
Bypass type	Internal bypass (automatic and manual)
Curve equation	Efficiency
Curve fixed loss	0,0229
Curve load maximum	100 %
Curve load minimum	3 %
Curve proportional loss	0,0382
Curve square loss	0,0289
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit to measured efficiency data. All measurements taken in normal operating mode, at typical environmental conditions, with nominal electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	2
Half load runtime	00:13:00 1200 W
Output voltage	230 V
Maximum configurable power in VA	3000 VA
Merkeffekt VA	3000 VA
Runtime at 600W	00:31:00

Conformance

Produktsertifikater	CE
Standarder	IEC 62040-1-1 IEC 62040-1-2

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 % non-condensing
Driftshøyde	0...3000 m
Omgivelsestemperatur for lagring	-20...50 °C
Storage Relative Humidity	0...95 % Ikke-kondenserende
Storage altitude	0...15000 m
Show note OP temperature	No

Batteries & Runtime

Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4 t

Communications & Management

Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

Packing Units

Enhetstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	9,6 kg
Forpakning 1 høyde	33 cm
Forpakning 1 bredde	23,5 cm
Forpakning 1 lengde	47,7 cm
Enhetstype forpakning 2	P12
Antall enheter forpakning 2	7
Forpakning 2 vekt	69,3 kg
Forpakning 2 høyde	45 cm
Forpakning 2 bredde	80 cm
Forpakning 2 lengde	120 cm

Contractual warranty

Garanti	2 years repair or replace
---------	---------------------------