



Overview

Presentasjon	For small to medium businesses, Easy UPS 1 Ph On-Line provides essential power protection for unstable power conditions, ensuring consistent and reliable connectivity at the most critical moments.
Leveringstid	Usually in Stock

General

Inkludert utstyr	CD with software User manual USB cable
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	S

Physical

Dybde	919,5 cm
Høyde	68,5 cm
Vekt	54 kg
Monteringsmetode	Not rack-mountable
USB compatible	No
Bredde	19 cm

Input

Network frequency	40...70 Hz
Number of input connectors	1 hard wire 3-wire
Input voltage limits	110...300 V half load 176...300 V fullastet
Inputvolt_other	220 V 240 V
Forsyningsspenning	230 V

Output

Merkeeffekt i W	6000 W
Maximum configurable power in W	6000 W
Output voltage	220 V 240 V
Crest faktor	3:1
UPS type	Double conversion online
Wave type	Sine wave
Curve equation	Efficiency
Curve load maximum	100 %

Curve X-axis maximum	100 %
Curve test cond ID	Curve fit to measured efficiency data. All measurements taken in normal operating mode, at typical environmental conditions, with nominal electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	2
Half load runtime	00:10:00 3000 W
Output voltage	230 V
Maximum configurable power in VA	6000 VA
Merkeeffekt VA	6000 VA

Conformance

Produktsertifikater	CE
Standarder	IEC 62040-1-1 IEC 62040-1-2

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 % non-condensing
Driftshøyde	0...3000 m
Storage Relative Humidity	0...95 % Ikke-kondenserende
Storage altitude	0...15000 m
Show note OP temperature	No

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0

Communications & Management

Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency power off	Yes

Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

Packing Units

Enhetstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	66 kg
Forpakning 1 høyde	91 cm
Forpakning 1 bredde	32 cm
Forpakning 1 lengde	58 cm
Enhetstype forpakning 2	P12
Antall enheter forpakning 2	16
Forpakning 2 vekt	251,5 kg
Forpakning 2 høyde	101 cm

Forpakning 2 bredde	80 cm
Forpakning 2 lengde	120 cm

Contractual warranty

Garanti	2 years repair or replace
---------	---------------------------