



Overview

Presentasjon	High density, double-conversion on-line power protection with scalable runtime.
Leveringstid	Usually in Stock

General

Inkludert utstyr	CD with software User manual USB cable
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Number of rack unit	2U
Farge	Black
Dybde	61,5 cm
Høyde	8,65 cm
Mounting preference	No preference
Vekt	16 kg
Monteringsmetode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes
Bredde	43,8 cm

Input

Network frequency	40...70 Hz
Number of input connectors	1 hard wire 3-wire
Input voltage limits	110...300 V half load 176...300 V fullastet
Inputvolt_other	220 V 240 V
Forsyningsspenning	230 V

Output

Merkeeffekt i W	10000 W
Maximum configurable power in W	10000 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Output voltage	220 V 240 V
Crest faktor	3:1
UPS type	Double conversion online
Wave type	Sine wave
Bypass type	Internal bypass (automatic and manual)
Effektivitet	(full load)
Output voltage	230 V
Maximum configurable power in VA	10000 VA
Merkeeffekt VA	10000 VA

Conformance

Produktsertifikater	CE
Standarder	IEC 62040-1-1 IEC 62040-1-2

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 % non-condensing
Driftshøyde	0...3000 m
Omgivelsestemperatur for lagring	-20...50 °C
Storage Relative Humidity	0...95 % Ikke-kondenserende
Storage altitude	0...15000 m
IP-grad	IP20

Batteries & Runtime

Batteritype	External battery system
Number of battery filled slots	0
Number of battery free slots	0
Liquid value	0
Batterispenningen	192 V
Battery curve	B
Battery power in VAh	0 VAh runtime
Extended runtime	0

Communications & Management

Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency power off	Yes

Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

Packing Units

Forpakning 1 vekt	20 kg
Forpakning 1 høyde	24 cm
Forpakning 1 bredde	60 cm
Forpakning 1 lengde	76 cm

Contractual warranty

Garanti	2 years repair or replace
---------	---------------------------