

SUM1500RMXLI2U

APC Smart-UPS XL Modular 1500VA 230V Rackmount/Tower



Overview

Presentasjon	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Leveringstid	Usually Ships within 4 Weeks

General

Inkludert utstyr	CD with software Installation guide Rack mounting brackets Rack mounting support rails Smart UPS signalling RS-232 cable User manual USB cable Web/SNMP management card
Product web sub-family	Network card pre-installed
Number of tare power	90 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Number of rack unit	2U
Farge	Black
Dybde	67,8 cm
Høyde	8,6 cm
Montasjeplassering	Front
Mounting preference	Lower
Vekt	46,82 kg
Monteringsmetode	Rack-mounted
Two post mountable	0
USB compatible	Yes
Bredde	43,2 cm

Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Plug standard	IEC 320 C14
Input voltage limits	151...302 V Justrbar 160...286 V
Antall kabler	1
Forsyningsspenning	230 V

Output

Merkeeffekt i W	1425 W
Maximum configurable power in W	1425 W
Harmonic distortion	Mindre enn 5 % ved full last
Output frequency	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	9 IEC 320 C13 2 IEC Jumpers
Bypass type	Internal bypass (automatic and manual)
Effektivitet	95 % (full load)
Maximum output current	15 A
Output voltage	230 V
Maximum configurable power in VA	1500 VA
Merkeeffekt VA	1500 VA

Conformance

Produktsertifikater	C-Tick CE GOST
Standarder	EN 50091-2 EN 55022 klasse A EN 61000-3-2

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-20...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0,00...9144,00 m
Akkustikknivå	55 dBA
Varmeavgivelse	300 Btu/t

Batteries & Runtime

Batteritype	VRLA
Number of battery filled slots	1
Number of battery free slots	0
Battery recharge time	3 t
Number of battery replacement quantity	1
Tilleggsinformasjon	Configurable for 220 : 230 or 240 nominal output voltage
Liquid value	0
Battery charger power	199 W rated
Battery power in VAh	600 VAh runtime
Batterilevetid	3...5 år
Battery option	SUM48RMXLBP2U 1 1440 VAh SUM48RMXLBP2U 2 2400 VAh SUM48RMXLBP2U 3 3360 VAh SUM48RMXLBP2U 4 4320 VAh SUM48RMXLBP2U 5 5280 VAh SUM48RMXLBP2U 6 6240 VAh SUM48RMXLBP2U 8 8160 VAh SUM48RMXLBP2U 10 10080 VAh
Extended runtime	1

Communications & Management

Ledige plasser	0
Preinstalled device	Network management card 2 with environmental monitoring
Control panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : overload and bypass indicators
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency power off	Optional

Surge Protection and Filtering

Surge energy rate	490 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Forpakning 1 vekt	56,82 kg
Forpakning 1 høyde	25 cm
Forpakning 1 bredde	59,6 cm
Forpakning 1 lengde	98 cm
Antall enheter forpakning 3	8

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Miljøinformasjon	 Produktmiljøprofil
Produktets livssyklus	 Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available

Contractual warranty

Garanti	2 years repair or replace
---------	---------------------------