



Overview

Leveringstid	Usually in Stock
--------------	------------------

General

Tilgjengelig utstyr	Installation guide Rack mounting brackets Brukermanual
---------------------	--

Physical

Farge	Sort
Dybde	66 cm
Høyde	17,8 cm
Vekt	21,36 kg
Bredde	43,2 cm

Input

Network frequency	50/60 Hz
Number of input connectors	1 hard wire 3-wire (H N + E) 1 hard wire 3-wire (2P + E) 1 hard wire 4-wire (2P + N + E) 1 hard wire 5-wire (3P + N + E)
Antall kabler	1
Permissible voltage	200...240 V
Max line current	100 A
Input current limits	100 A
Load capacity	20000 VA
18 mm avstand	0...1
Forsyningsspenning	200 V 208 V 230 V 3 faser

Output

Max current draw	100 A
Output connector type	Hard wire 3-wire (H N + E) 1 Hard wire 3-wire (2P + E) 1 Hard wire 4-wire (2P + N + E) 1
Type vern	Strømbryter
Effektivitet	99 %
Output voltage	120 V 200 V 208 V 230 V

Conformance

Produktsertifikater	CSA GOST
Standarder	EN 60950 IEC 60950 IEC 60950 UL 1778

Environmental

Omgivelsestemperatur drift	-20...50 °C
Relativ fuktighet	0...95 %
Driftshøyde	0...15000 ft
Omgivelsestemperatur for lagring	-40...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0,00...15240,00 m

Packing Units

Forpakning 1 vekt	31,36 kg
Forpakning 1 høyde	30,5 cm
Forpakning 1 bredde	61 cm
Forpakning 1 lengde	99,1 cm

Offer Sustainability

EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
------------------	---

Contractual warranty

Garanti	2 years (parts only)
---------	----------------------