



Overview

Leveringstid	Usually in Stock
--------------	------------------

General

Inkludert utstyr	User manual
Max runtime	28 min
Number of tare power	6 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS

Physical

Kabellengde	1,83 m
Farge	Black
Dybde	21,3 cm
Høyde	18,5 cm
Mounting preference	No preference
Vekt	5,2 kg
Monteringsmetode	Not rack-mountable
Two post mountable	0
USB compatible	No
Bredde	11,5 cm

Input

Network frequency	45...65 Hz
Plug standard	IEC 60320 C14
Input voltage limits	160...280 V
Maximum input current	2 A
Brytekapasitet, A	7 A
Antall kabler	1
Forsyningsspenning	230 V

Output

Merkeeffekt i W	300 W
Maximum configurable power in W	300 W
Output frequency	50 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Nb of power socket outlets	3 IEC 60320 C13 1 IEC Jumpers
Curve equation	Efficiency
Curve fixed loss	0,0098
Curve load maximum	100 %
Curve load minimum	1 %
Curve proportional loss	0
Curve square loss	0,0038
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit to measured efficiency data. All measurements taken in normal operating mode, at typical environmental conditions, with nominal electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	230 V
Maximum configurable power in VA	500 VA
Merkeeffekt VA	500 VA
Transfer time	6 ms typical : 10 ms maximum

Conformance

Produktsertifikater	CE GOST NEMKO
Standarder	EN/IEC 60950-1

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0,00...15240,00 m
Akkustikknivå	45 dBA
Show note OP temperature	No

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Liquid value	0
Battery curve	C
Battery charger power	4700 W rated
Battery power in VAh	47 VAh runtime
Extended runtime	0

Communications & Management

Control panel	LED Status display with on line : on battery
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	273 J
-------------------	-------

Packing Units

Forpakning 1 vekt	5,68 kg
Forpakning 1 høyde	25,7 cm
Forpakning 1 bredde	19 cm
Forpakning 1 lengde	29,1 cm
SCC14	60731304307428
Antall enheter forpakning 3	60

Offer Sustainability

REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available

Contractual warranty

Garanti	2 years repair or replace
---------	---------------------------