



Overview

Presentasjon	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Leveringstid	Usually Ships within 2 Weeks

General

Inkludert utstyr	CD with software Documentation CD Smart UPS signalling RS-232 cable USB cable
Number of tare power	15 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Kabellengde	1,83 m
Farge	Black
Dybde	35,81 cm
Høyde	15,75 cm
Montasjeplassering	Front
Mounting preference	No preference
Vekt	13,18 kg
Monteringsmetode	Not rack-mountable
Two post mountable	0
USB compatible	Yes
Bredde	13,8 cm

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	IEC 320 C14
Input voltage limits	151...302 V Justbar 160...280 V
Inputvolt_other	220 V 240 V
Antall kabler	1
Forsyningsspenning	230 V

Output

Merkeeffekt i W	500 W
Maximum configurable power in W	500 W
Harmonic distortion	Mindre enn 5 % ved full last
Output frequency	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains
Output voltage	220 V 240 V
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	6 IEC 320 C13 2 IEC Jumpers
Output voltage	230 V
Maximum configurable power in VA	750 VA
Merkeeffekt VA	750 VA
Transfer time	4 ms typical : 8 ms maximum

Conformance

Produktsertifikater	CE EAC RCM VDE
Standarder	EN/IEC 62040-1 EN/IEC 62040-2

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0,00...15240,00 m
Akkustikknivå	40 dBA
Varmeavgivelse	90 Btu/t

Batteries & Runtime

Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 t
Number of battery replacement quantity	1
Liquid value	0
Battery charger power	49 W rated
Battery power in VAH	146 VAh runtime
Batterilevetid	3...5 år
Extended runtime	0

Communications & Management

Ledige plasser	1
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency power off	Optional

Surge Protection and Filtering

Surge energy rate	540 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Forpakning 1 vekt	14,23 kg
Forpakning 1 høyde	30,1 cm
Forpakning 1 bredde	27,8 cm
Forpakning 1 lengde	49,9 cm
SCC14	731304269069
Antall enheter forpakning 3	24

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Miljøinformasjon	 Produktmiljøprofil
Produktets livssyklus	 Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available

Contractual warranty

Garanti	3 years repair or replace (excluding battery) and 2 years for battery
---------	---