



Overview

Presentasjon	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Leveringstid	Usually in Stock

General

Inkludert utstyr	CD with software Documentation CD Smart UPS signalling RS-232 cable USB cable
Number of tare power	55 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Number of rack unit	0U
Farge	Black
Dybde	54,4 cm
Høyde	43,5 cm
Montasjeplassering	Front
Mounting preference	No preference
Vekt	52,5 kg
Monteringsmetode	Not rack-mountable
Two post mountable	0
USB compatible	Yes
Bredde	19,7 cm

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	IEC 320 C20 Schuko CEE 7 / EU1-16P BS1363A British
Input voltage limits	151...302 V Justrbar 160...286 V
Inputvolt_other	220 V 240 V
Antall kabler	1
Forsyningsspenning	230 V

Output

Merkeeffekt i W	2700 W
Maximum configurable power in W	2700 W
Harmonic distortion	Mindre enn 5 % ved full last
Output frequency	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	8 IEC 320 C13 2 IEC Jumpers 1 IEC 320 C19
Output voltage	230 V
Maximum configurable power in VA	3000 VA
Merkeeffekt VA	3000 VA
Transfer time	2 ms typical

Conformance

Produktsertifikater	CE CSA EAC RCM VDE
Standarder	EN/IEC 62040-1 EN/IEC 62040-2

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0,00...15240,00 m
Akkustikknivå	53 dBA
Varmeavgivelse	375 Btu/t

Batteries & Runtime

Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 t
Number of battery replacement quantity	1
Tilleggsinformasjon	Configurable for 220 : 230 or 240 nominal output voltage
Liquid value	0
Battery charger power	271 W rated
Battery power in VAH	816 VAh runtime
Batterilevetid	3...5 år
Extended runtime	1

Communications & Management

Ledige plasser	1
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency power off	Yes

Surge Protection and Filtering

Surge energy rate	365 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Forpakning 1 vekt	63,7 kg
Forpakning 1 høyde	69,9 cm
Forpakning 1 bredde	38,1 cm
Forpakning 1 lengde	76,2 cm
SCC14	731304268710
Antall enheter forpakning 3	9

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Miljøinformasjon	 Produktmiljøprofil
Produktets livssyklus	 Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available

Contractual warranty

Garanti	3 years repair or replace (excluding battery) and 2 years for battery, optional on-site warranties available, optional extended warranties available
---------	--