



Overview

Leveringstid	Usually in Stock
--------------	------------------

General

Inkludert utstyr	CD with software 1 x detachable IEC power cord User manual USB cable Warranty card
Performance multiplier	1
Number of tare power	10 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
Size UPS version	Workstation
UPS size	WS
Value multiplier	1

Physical

Farge	Black
Dybde	38,2 cm
Høyde	25 cm
Mounting preference	No preference
Vekt	10,72 kg
Monteringsmetode	Not rack-mountable
Two post mountable	0
USB compatible	No
Bredde	10 cm

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	IEC 60320 C14
Input voltage limits	156...300 V Justrbar 176...294 V
Maximum input current	8 A
Brytekapasitet, A	10 A
Antall kabler	1
Forsyningsspenning	230 V

Output

Merkeeffekt i W	540 W
Maximum configurable power in W	540 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains 50/60 Hz +/- 1 Hz unsynchronised
Crest faktor	3:1
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Nb of power socket outlets	4 IEC 60320 C13 4 IEC 60320 C13 surge 2 IEC Jumpers
Bypass type	Built-in bypass
Curve equation	Efficiency
Curve fixed loss	0,0222
Curve load maximum	100 %
Curve load minimum	3 %
Curve proportional loss	0
Curve square loss	0,0041
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit to measured efficiency data. All measurements taken in normal operating mode, at typical environmental conditions, with nominal electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	230 V
Maximum configurable power in VA	900 VA
Merkeeffekt VA	900 VA
Transfer time	8 ms typical : 10 ms maximum

Conformance

Produktsertifikater	A-Tick C-Tick CE
Merking	GS Mark
Equipment protection policy	Lifetime : 200000 AUD Lifetime : 150000 euros Lifetime : 75000 GBP

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 %
Driftshøyde	0...9842 ft
Omgivelsestemperatur for lagring	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0,00...14999,82 m
Akkustikknivå	45 dBA
Show note OP temperature	No

Batteries & Runtime

Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 t
Number of battery replacement quantity	1
Liquid value	0
Batterispenningen	24 V
Kapasitet på batteri	7,0 Ah
Battery curve	B
Battery charger power	20 W rated
Battery power in VAH	157 VAh runtime
Batterilevetid	3...5 år
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v
Extended runtime	0

Communications & Management

Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	613 J
Noise suppression	Full time multi-pole noise filtering : 10% of IEEE surge let-through : zero clamping response time: instantaneous
Data line protection	RJ11 analog phone line for phone/fax/modem/DSL RJ45 network line - 10/100/1000 Base-T Ethernet

Packing Units

Forpakning 1 vekt	11,7 kg
Forpakning 1 høyde	33,7 cm
Forpakning 1 bredde	22,5 cm
Forpakning 1 lengde	48,7 cm
SCC14	10731304279591
Antall enheter forpakning 2	1
Antall enheter forpakning 3	30
Forpakning 3 vekt	393,28 kg
Forpakning 3 lengde	116,84 cm

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	REACH-erklæring
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	Ja
Miljøinformasjon	Produktmiljøprofil
Produktets livssyklus	Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available

Contractual warranty

Garanti

2 years repair or replace, 3 years repair or replace for European Union countries