



Overview

Leveringstid	Usually in Stock
--------------	------------------

General

Inkludert utstyr	CD with software Documentation CD 1 x detachable IEC power cord 1 x detachable 1.2 m IEC power cord Telephone cable USB cable Warranty card
Max runtime	45 min
Performance multiplier	1
Number of tare power	14 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
Size UPS version	Internetworking Workstation
UPS size	WS
Value multiplier	1

Physical

Farge	Beige
Dybde	28,4 cm
Høyde	16,5 cm
Montasjeplassering	Front
Mounting preference	No preference
Vekt	6,32 kg
Monteringsmetode	Not rack-mountable
Two post mountable	0
USB compatible	No
Bredde	9,1 cm

Input

Network frequency	47...63 Hz 50/60 Hz +/- 3 Hz auto-sensing
Plug standard	IEC 60320 C14
Input voltage limits	160...300 V Justrbar 180...266 V
Maximum input current	7 A
Brytekapasitet, A	7 A
Antall kabler	2
Forsyningsspenning	230 V

Output

Merkeeffekt i W	300 W
Maximum configurable power in W	300 W
Output frequency	47...63 Hz sync to mains 50/60 Hz +/- 1 Hz unsynchronised
UPS type	Standby
Wave type	Stepped approximation to a sinewave
Nb of power socket outlets	3 IEC 60320 C13 1 IEC 60320 C13 surge 2 IEC Jumpers surge
Curve equation	Efficiency
Curve fixed loss	0,0093
Curve load maximum	100 %
Curve load minimum	1 %
Curve proportional loss	0
Curve square loss	0,0012
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 230V/50Hz electrical input and balanced resistive load (PF =
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	230 V
Maximum configurable power in VA	500 VA
Merkeeffekt VA	500 VA
Transfer time	6 ms typical : 10 ms maximum

Conformance

Produktsertifikater	C-Tick CE GOST VDE
Standarder	EN 50091-1 EN 50091-2
Equipment protection policy	Lifetime : 100000 euros Lifetime : 50000 GBP

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0,00...15240,00 m
Akkustikknivå	40 dBA
Varmeavgivelse	24 Btu/t
Show note OP temperature	No

Batteries & Runtime

Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 t
Number of battery replacement quantity	1
Liquid value	0
Batterispenningen	12 V
Kapasitet på batteri	7,0 Ah
Battery curve	B
Battery charger power	10 W rated
Battery power in VAH	83 VAh capacity 84 VAh runtime
Batterilevetid	4...6 år
Extended runtime	0

Communications & Management

Ledige plasser	0
Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	310 J
Noise suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Data line protection	RJ45 analog phone line for phone/fax/modem/DSL

Packing Units

Forpakning 1 vekt	7,05 kg
Forpakning 1 høyde	17,8 cm
Forpakning 1 bredde	24,1 cm
Forpakning 1 lengde	36,8 cm
SCC14	10731304016356
Antall enheter forpakning 2	1
Antall enheter forpakning 3	48

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
EU RoHS-direktiv	Proaktivt i samsvar (Produktet inngår ikke i EUs RoHS direktivet) EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	Ja
Miljøinformasjon	Produktmiljøprofil
Produktets livssyklus	Informasjon Om Levetidsslutt
Optimalisert energieffektivitet	Energieffektivt produkt

Contractual warranty

Garanti	2 years repair or replace
---------	---------------------------