



Overview

Presentasjon	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Leveringstid	Usually Ships within 2 Weeks

General

Inkludert utstyr	CD with software Documentation CD Installation guide Rack mounting brackets Removable support feet Smart UPS signalling RS-232 cable USB cable
Product web sub-family	Extended run
Number of tare power	7 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Kabellengde	1,83 m
Number of rack unit	2U
Farge	Black
Dybde	49 cm
Høyde	8,9 cm
Mounting preference	Lower
Vekt	22,86 kg
Monteringsmetode	Rack-mounted with kit
Two post mountable	1
USB compatible	No
Bredde	43,2 cm

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	IEC 320 C14
Input voltage limits	151...302 V Justerbar 160...286 V
Antall kabler	1
Forsyningsspenning	230 V

Output

Merkeeffekt i W	800 W
Maximum configurable power in W	800 W
Harmonic distortion	Mindre enn 5 %
Output frequency	50/60 Hz +/- 3 Hz sync to mains
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	8 IEC 320 C13 2 IEC Jumpers
Output voltage	230 V
Maximum configurable power in VA	1000 VA
Merkeeffekt VA	1000 VA

Conformance

Produktsertifikater	CE RCM VDE EAC
Standarder	EN/IEC 62040-1 EN/IEC 62040-2

Environmental

Omgivelsestemperatur drift	0...45 °C
Relativ fuktighet	0...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0,00...15240,00 m
Akkustikknivå	40 dBA
Varmeavgivelse	82 Btu/t

Batteries & Runtime

Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 t
Number of battery replacement quantity	1
Liquid value	0
Beskyttelse mot overstrøm	60 A
Battery charger power	99 W rated
Battery power in VAh	299 VAh runtime
Batterilevetid	3...5 år
Battery option	SMX48RMBP2U 1 900 VAh SMX48RMBP2U 2 1500 VAh SMX48RMBP2U 3 2100 VAh SMX48RMBP2U 4 2700 VAh SMX48RMBP2U 5 3300 VAh
Extended runtime	0

Communications & Management

Ledige plasser	1
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency power off	Yes

Surge Protection and Filtering

Surge energy rate	600 J
Noise suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Forpakning 1 vekt	27,32 kg
Forpakning 1 høyde	24,6 cm
Forpakning 1 bredde	58,9 cm
Forpakning 1 lengde	62 cm
Antall enheter forpakning 3	8

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Miljøinformasjon	 Produktmiljøprofil
Produktets livssyklus	 Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available

Contractual warranty

Garanti	3 years repair or replace (excluding battery) and 2 years for battery
---------	---