



Overview

Leveringstid	Usually in Stock
--------------	------------------

General

Inkludert utstyr	CD with software Telephone cable User manual
Max runtime	6 min
Performance multiplier	1
Number of tare power	17 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS
Value multiplier	1

Physical

Kabellengde	1,83 m
Farge	Black
Dybde	31,1 cm
Høyde	8,9 cm
Mounting preference	No preference
Vekt	6,02 kg
Monteringsmetode	Not rack-mountable
Two post mountable	0
USB compatible	Yes
Bredde	22,4 cm

Input

Network frequency	50/60 Hz
Plug standard	Schuko CEE 7/7P
Input voltage limits	180...266 V
Maximum input current	10 A
Brytekapasitet, A	10 A
Forsyningsspenning	230 V

Output

Merkeeffekt i W	330 W
Maximum configurable power in W	330 W
Output frequency	47...63 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
UPS type	Standby
Wave type	Stepped approximation to a sinewave
Nb of power socket outlets	4 Schuko CEE 7 4 Schuko CEE 7 surge
Utgangsspenning toleranse	+/- 5% static and 100% load step
Curve equation	Efficiency
Curve fixed loss	0,0127
Curve load maximum	100 %
Curve load minimum	2 %
Curve proportional loss	0
Curve square loss	0,0004
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 230V/50Hz electrical input and balanced resistive load (PF =
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	230 V
Maximum configurable power in VA	550 VA
Merkeeffekt VA	550 VA
Transfer time	6 ms typical : 10 ms maximum

Conformance

Produktsertifikater	CE
Equipment protection policy	Lifetime : 100000 euros

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 %
Driftshøyde	0...30000 ft
Omgivelsestemperatur for lagring	-15...40 °C
Storage Relative Humidity	0...95 %
Storage altitude	0,00...9144,00 m
Akkustikknivå	40 dBA
Show note OP temperature	No

Batteries & Runtime

Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	16 t
Liquid value	0
Batterispenningen	12 V

Kapasitet på batteri	7,0 Ah
Battery curve	B
Battery charger power	5 W rated
Battery power in VAH	86 VAh runtime
Batterilevetid	3...5 år
Extended runtime	0

Communications & Management

Control panel	LED status display with on line : on battery : replace battery and overload indicators
---------------	--

Surge Protection and Filtering

Surge energy rate	310 J
Noise suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Data line protection	RJ11 analog phone line for phone/fax/modem/DSL RJ45 network line - 10/100 base-T Ethernet

Packing Units

Forpakning 1 vekt	6,93 kg
Forpakning 1 høyde	12,7 cm
Forpakning 1 bredde	27,9 cm
Forpakning 1 lengde	40 cm
SCC14	10731304271663
Antall enheter forpakning 2	2
Forpakning 2 vekt	14,51 kg
Forpakning 2 lengde	323,85 mm
Antall enheter forpakning 3	48
Forpakning 3 vekt	559,09 kg
Forpakning 3 lengde	121,92 cm
Antall enheter på en pall	20
Antall pallegag	4

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Miljøinformasjon	 Produktmiljøprofil
Produktets livssyklus	 Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available

Contractual warranty

Garanti	2 years repair or replace, 3 years repair or replace for European Union countries
---------	---