



### Overview

|              |                                                                                                                                                                                                                |
|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Presentasjon | For small to medium businesses,&nbsp;Easy UPS 1 Ph On-Line&nbsp;provides essential power protection for unstable power conditions, ensuring consistent and reliable connectivity at the most critical moments. |
| Leveringstid | Usually in Stock                                                                                                                                                                                               |

### General

|                                     |                                                                                                             |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------|
| Inkludert utstyr                    | Basic UPS signalling RS-232 cable<br>CD with software<br>Rack mounting brackets<br>User manual<br>USB cable |
| Number of tare power                | 60 W                                                                                                        |
| Number of power module free slots   | 0                                                                                                           |
| Number of power module filled slots | 0                                                                                                           |
| Redundant                           | No                                                                                                          |

### Physical

|                     |                       |
|---------------------|-----------------------|
| Number of rack unit | 4U                    |
| Farge               | Black                 |
| Dybde               | 61,5 cm               |
| Høyde               | 17,3 cm               |
| Vekt                | 61 kg                 |
| Monteringsmetode    | Rack-mounted with kit |
| USB compatible      | Yes                   |
| Bredde              | 43,8 cm               |

### Input

|                            |                                                |
|----------------------------|------------------------------------------------|
| Network frequency          | 40...70 Hz                                     |
| Number of input connectors | 1 hard wire 3-wire                             |
| Input voltage limits       | 110...300 V half load<br>176...300 V fullastet |
| Inputvolt_other            | 220 V<br>240 V                                 |
| Forsyningsspenning         | 230 V                                          |

### Output

|                                 |                                 |
|---------------------------------|---------------------------------|
| Merkeeffekt i W                 | 6000 W                          |
| Maximum configurable power in W | 6000 W                          |
| Output frequency                | 50/60 Hz +/- 3 Hz sync to mains |
| Output voltage                  | 220 V<br>240 V                  |
| Crest faktor                    | 3:1                             |

|                                  |                                        |
|----------------------------------|----------------------------------------|
| UPS type                         | Double conversion online               |
| Wave type                        | Sine wave                              |
| Output connector type            | Hard wire 3-wire (H N + E) 1           |
| Bypass type                      | Internal bypass (automatic and manual) |
| Effektivitet                     | 94 % (full load)                       |
| Half load runtime                | 00:10:00 3000 W                        |
| Output voltage                   | 230 V                                  |
| Maximum configurable power in VA | 6000 VA                                |
| Merkeeffekt VA                   | 6000 VA                                |

## Conformance

|                     |                                |
|---------------------|--------------------------------|
| Produktsertifikater | CE                             |
| Standarder          | IEC 62040-1-1<br>IEC 62040-1-2 |

## Environmental

|                                  |                             |
|----------------------------------|-----------------------------|
| Omgivelsestemperatur drift       | 0...40 °C                   |
| Relativ fuktighet                | 0...95 % non-condensing     |
| Driftshøyde                      | 0...3000 m                  |
| Omgivelsestemperatur for lagring | -15...60 °C                 |
| Storage Relative Humidity        | Ikke-kondenserende 0...95 % |
| Storage altitude                 | 0...15000 m                 |
| Akkustikknivå                    | 55 dB                       |
| IP-grad                          | IP20                        |

## Batteries & Runtime

|                                |                                                          |
|--------------------------------|----------------------------------------------------------|
| Batteritype                    | Bly-syre batteri                                         |
| Number of battery filled slots | 0                                                        |
| Number of battery free slots   | 0                                                        |
| Battery recharge time          | 3 t                                                      |
| Tilleggsinformasjon            | Configurable for 220 : 230 or 240 nominal output voltage |
| Liquid value                   | 0                                                        |
| Battery curve                  | D                                                        |
| Battery charger power          | 373 W rated                                              |

## Communications & Management

|                     |                                                                                        |
|---------------------|----------------------------------------------------------------------------------------|
| Ledige plasser      | 1                                                                                      |
| Control panel       | Multifunction LCD status and control console                                           |
| Alarm               | Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm |
| Emergency power off | Yes                                                                                    |

## Surge Protection and Filtering

|                   |       |
|-------------------|-------|
| Surge energy rate | 600 J |
|-------------------|-------|

## Packing Units

|                             |         |
|-----------------------------|---------|
| Enhetstype forpakning 1     | PCE     |
| Antall enheter forpakning 1 | 1       |
| Forpakning 1 vekt           | 71 kg   |
| Forpakning 1 høyde          | 48,5 cm |
| Forpakning 1 bredde         | 60 cm   |
| Forpakning 1 lengde         | 83,6 cm |

## Contractual warranty

|         |                           |
|---------|---------------------------|
| Garanti | 2 years repair or replace |
|---------|---------------------------|