



Overview

Presentasjon	For small to medium businesses, Easy UPS 1 Ph On-Line provides essential power protection for unstable power conditions, ensuring consistent and reliable connectivity at the most critical moments.
Leveringstid	Usually in Stock

General

Inkludert utstyr	Basic UPS signalling RS-232 cable CD with software Rack mounting support rails User manual USB cable
Max runtime	4 min
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS

Physical

Kabellengde	1,50 m
Number of rack unit	2U
Farge	Black
Dybde	31,2 cm
Høyde	8,6 cm
Vekt	11 kg
Monteringsmetode	Rack-mounted
USB compatible	Yes
Bredde	43,7 cm

Input

Network frequency	40...70 Hz
Plug standard	IEC 60320 C14
Input voltage limits	110...285 V half load 160...280 V fullastet
Inputvolt_other	220 V 240 V
Antall kabler	1
Forsyningsspenning	230 V

Output

Merkeeffekt i W	800 W
Maximum configurable power in W	800 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Output voltage	220 V 240 V
Crest faktor	3:1
UPS type	Double conversion online
Wave type	Sine wave
Nb of power socket outlets	3 IEC 60320 C13
Bypass type	Internal bypass (automatic and manual)
Curve equation	Efficiency
Curve fixed loss	0,0468
Curve load maximum	100 %
Curve load minimum	5 %
Curve proportional loss	0,0447
Curve square loss	0,0209
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit to measured efficiency data. All measurements taken in normal operating mode, at typical environmental conditions, with nominal electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Effektivitet	88 % (fullastet)
Graph display	1
Output voltage	230 V
Maximum configurable power in VA	1000 VA
Merkeeffekt VA	1000 VA
Runtime at 200W	00:24:00
Runtime at 400W	00:11:00

Conformance

Produktsertifikater	CE
Standarder	IEC 62040-1-1 IEC 62040-1-2

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 % non-condensing
Driftshøyde	0...3000 m
Omgivelsestemperatur for lagring	-20...50 °C
Storage Relative Humidity	0...95 % Ikke-kondenserende
Storage altitude	0...15000 m
Akkustikknivå	50 dB
Show note OP temperature	No
IP-grad	IP20

Batteries & Runtime

Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4 t
Tilleggsinformasjon	Configurable for 220 : 230 or 240 nominal output voltage
Batterispenningen	24 V
Battery charger power	38 W rated

Communications & Management

Ledige plasser	1
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

Packing Units

Enhetstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	13,1 kg
Forpakning 1 høyde	21,8 cm
Forpakning 1 bredde	45,5 cm
Forpakning 1 lengde	55,1 cm
Enhetstype forpakning 2	P06
Antall enheter forpakning 2	1
Forpakning 2 vekt	13,1 kg
Forpakning 2 høyde	36 cm
Forpakning 2 bredde	60 cm
Forpakning 2 lengde	80 cm

Contractual warranty

Garanti	2 years repair or replace
---------	---------------------------