



Teknisk informasjon

Serie	Actassi
Product type	RJ45 nettverksuttak
Enhetens utseende	En enhet, ingen løse deler
Fargetone	Wire organizer: dark blue (ABS + PC) Connector: dark grey (ABS + PC) Connector housing: translucent (ABS + PC)
Wiring Colour configuration	568 A/B
Forpakning	Individual bag
Antall pr. sett	Sett á 1

Komplementær

[In] merkestrøm	1.5 A at 25 °C
Voltage proof	1000 V AC/DC peak, between contacts
Contact resistance	20 mOhm
Isolasjonsmotstand	Initial insulation resistance: ≥ 500 MOhm at 100 V DC
AWG gauge	AWG 23...AWG 24
Durability	750 cycles
Koblingsdemping	≥ 35 dB at 30...100 MHz $\geq 75 - 20 \times \log(f)$ dB at 100...1000 MHz
Contact pins	8 pins of copper alloy and gold plated conforming to IEC 60603-7
Trekraft	50 N during 60 s
Transersalt konverteringstap	≥ 50 dB $\geq 68 - 20 \times \log(f)$ dB at 1...500000 kHz
Verktøy type	Uten verktøy
Kabelens ytre diameter	0,9...1,4 mm
Compatible LAN cable types	UTP
Nettverkskategori	6A
Supported applications	10GBASE-T
Protocols	VoIP (Voice IP) PoE+ (Power over Ethernet) 4PPoE 100W (Power over Ethernet)
Overføringsfrekvens	0...500 MHz
Type footprint	S-One DPM
Høyde	28 mm
Lengde	33 mm
Bredde	18 mm
Gjeldende land	Europe

Miljø

Operational temperature range	-40...70 °C
Climatic category	40/070/21 (21 days)
Flammehemming	UL94-V0
Standarder	ANSI/TIA-568-C.2 AS/NZS 3080 AS/CA S008 ISO/IEC 11801 IEC 60603-7-41 EN 50173

Packing Units

Enhetstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	13,4 g
Forpakning 1 høyde	2,8 cm
Forpakning 1 bredde	3,3 cm
Forpakning 1 lengde	1,8 cm
Enhetstype forpakning 2	S04
Antall enheter forpakning 2	320
Forpakning 2 vekt	11,256 kg
Forpakning 2 høyde	30 cm
Forpakning 2 bredde	40 cm
Forpakning 2 lengde	60 cm

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
REACH fri for SVHC	Ja
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Fri for giftige tungmetaller	Ja
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Kinas RoHS-forskrift	 Kinas RoHS-Erklæring
Miljøinformasjon	 Produktmiljøprofil
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.

Contractual warranty

Garanti	18 months
---------	-----------