



### Overview

Presentasjon	High-efficiency 3-phase UPS that features advanced product features, competitive specifications, and robust electrical design, making business continuity easy in the data center or electrical room. This is an exceptionally easy to install, operate, maintain, and service 30 kVA UPS, ideal for small and medium businesses. Includes dust filter and conformance-coated boards for harsh environments. This UPS is supplied without batteries, so you can easily customize the battery solution.
Leveringstid	Usually Ships within 6 Weeks

### General

Inkludert utstyr	Dust filter Installation guide
UPS size	WS

### Physical

Farge	White (RAL 9003)
Dybde	80 cm
Høyde	77 cm
Vekt	60 kg
USB compatible	Yes
Bredde	25 cm

### Input

Network frequency	45...65 Hz
Input voltage limits	304...477 V
Inputvolt_other	380 V 415 V
Maximum input current	55 A
Forsyningsspenning	3 faser
Load power factor	0.9 leading to 0.9 lagging
Cos phi	0,99

### Output

Merkeeffekt i W	30000 W
Maximum configurable power in W	30000 W
Harmonic distortion	Mindre enn 3 %
Output frequency	50 Hz sync to mains 60 Hz sync to mains
Output voltage	380 V 415 V
Crest faktor	3:1
UPS type	Double conversion online
Output overload operation	10 minutes at 125% and 60 seconds at 150%
Bypass type	Built-in maintenance bypass
Curve equation	Efficiency

Curve fixed loss	0,0057
Curve load maximum	100 %
Curve load minimum	1 %
Curve proportional loss	0,0209
Curve square loss	0,0256
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit to measured efficiency data. All measurements taken in normal operating mode, at typical environmental conditions, with 400V 50Hz input and 400V 50Hz balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	400 V 3 faser
Maximum configurable power in VA	30000 VA
Merkeeffekt VA	30000 VA

## Conformance

Produktsertifikater	CE EAC RCM
Standarder	IEC 62040-1-1 IEC 62040-2 IEC 62040-3 IEC 62040-4 ISTA 2B

## Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 % non-condensing
Driftshøyde	0...3281 ft
Omgivelsestemperatur for lagring	-15...40 °C
Storage Relative Humidity	Ikke-kondenserende 0...95 %
Storage altitude	0,00...14999,82 m
Akkustikknivå	63 dBA
Varmeavgivelse	1410 Btu/t
Show note OP temperature	No
IP-grad	IP20

## Batteries & Runtime

Batteritype	External battery system
Number of battery filled slots	0
Number of battery free slots	0
Maximum short-circuit current	10 kA

## Packing Units

Forpakning 1 vekt	76,839 kg
Forpakning 1 høyde	100,000 cm
Forpakning 1 bredde	40,000 cm
Forpakning 1 lengde	97,000 cm

## Offer Sustainability

REACH-regelverk	<a href="#">REACH-erklæring</a>
EU RoHS-direktiv	Proaktivt i samsvar (Produktet inngår ikke i EUs RoHS direktivet) <a href="#">EU RoHS-erklæring</a>
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	<a href="#">Ja</a>
Kinas RoHS-forskrift	<a href="#">Kinas RoHS-Erklæring</a>
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt

## Contractual warranty

Garanti	1 year on-site repair or replace with factory authorized Start-Up
---------	---