



Overview

Leveringstid	Usually in Stock
--------------	------------------

General

Inkludert utstyr	User manual
Number of tare power	30 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS

Physical

Kabellengde	1,16 m
Dybde	33,6 cm
Høyde	21,5 cm
Mounting preference	No preference
Vekt	8 kg
Monteringsmetode	Not rack-mountable
Two post mountable	0
USB compatible	No
Bredde	13 cm

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	Schuko CEE 7/7P
Input voltage limits	150...280 V
Maximum input current	3 A
Brytekapasitet, A	7 A
Forsyningsspenning	230 V

Output

Merkeeffekt i W	480 W
Maximum configurable power in W	480 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains 50/60 Hz +/- 1 Hz unsynchronised
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Nb of power socket outlets	4 Schuko CEE 7

Curve equation	Efficiency
Curve fixed loss	0,0301
Curve load maximum	100 %
Curve load minimum	4 %
Curve proportional loss	0
Curve square loss	0,0064
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit to measured efficiency data. All measurements taken in normal operating mode, at typical environmental conditions, with nominal electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	230 V
Maximum configurable power in VA	800 VA
Merkeeffekt VA	800 VA
Transfer time	8 ms typical : 12 ms maximum

Conformance

Produktsertifikater	CE GOST NEMKO
Standarder	EN/IEC 60950-1

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0,00...9144,00 m
Akkustikknivå	45 dBA
Show note OP temperature	No

Batteries & Runtime

Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 t
Number of battery replacement quantity	1
Liquid value	0
Battery curve	C
Battery charger power	11 W rated
Battery power in VAH	88 VAh runtime
Batterilevetid	3...5 år
Extended runtime	0

Communications & Management

Control panel	LED Status display with on line : on battery
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	273 J
-------------------	-------

Packing Units

Forpakning 1 vekt	8,79 kg
Forpakning 1 høyde	29,5 cm
Forpakning 1 bredde	24,5 cm
Forpakning 1 lengde	44 cm
SCC14	60731304307862

Offer Sustainability

REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available

Contractual warranty

Garanti	2 years repair or replace
---------	---------------------------