FEATURES AND SPECIFICATIONS

molex

Patch cord RJ45, 568B, F/UTP, Stranded, PowerCat 5e, LS0H

Features and Benefits

Molex PowerCat 5e Shielded Patch Cords are key components of the PowerCat 5e shielded end-to-end solution. Molex PowerCat 5e Patch Cords are designed to support high speed networks. The patch cable is made from high quality four pair 26 AWG stranded copper wire. Available in a range of colours and lengths, PowerCat 5e patch cords are pre-terminated with RJ45 plugs and feature antisnag slim strain relief slip on boots.

- 4 pair 26 AWG stranded copper wire
- Pre-terminated with RJ45 plugs
- Slim clear anti-snag slip on boots
- Suitable for EIA 568A or 568B wiring
- LS0H sheath
- RoHS Compliant

Commerical Standards

ISO/IEC 11801 2nd Ed Amd 1 Class D TIA-568-C.2 Cat. 5e, EN50173 Cat.5e

Pending Approvals
UL 1863; CSA C22.2

Fire Propagation Tests

IEC 60332-1, IEC 61034-2, IEC-60754-1, IEC-60754-2

Technical Information

Mechanical Characteristics - Cable

Conductor size: 26 AWG stranded

copper wire

Screen material: Aluminum/polyester

shield with tinned

copper drain wire

Nom. O.D.: max 5.5mm Sheath: Low Smoke Zero

Halogen (LS0H)

Bend radius: 8X O.D. Operating temperature range:

-20°C to 60°C

Mechanical Characteristics - Plug

MIN operating life: 750 insertion cycles RJ45 plug material: Clearpolycarbonate

(PC)

Boot material: Clear polyvinylchlo-

ride (PVC)

Contact material: 0.35mm thick copper


Contact plating: 1.27um gold

RJ45 plug dimensions compliant with:

ISO/IEC 60603-7 and FCC 47 Part 68

Electrical Characteristics

Max voltage: 150 VAC (max)
Max current: 1.5A @ 25°C



ORDERING INFORMATION

Order No.	Description
PCD-03001-*	Patch cord RJ45, 568B, F/UTP, Stranded, PowerCat 5e, LS0H 1m
PCD-03003-*	Patch cord RJ45, 568B, F/UTP, Stranded, PowerCat 5e, LS0H 2m
PCD-03005-*	Patch cord RJ45, 568B, F/UTP, Stranded, PowerCat 5e, LS0H 3m
PCD-03009-*	Patch cord RJ45, 568B, F/UTP, Stranded, PowerCat 5e, LS0H 5m
PCD-03013-*	Patch cord RJ45, 568B, F/UTP, Stranded, PowerCat 5e, LS0H 7m
PCD-03019-*	Patch cord RJ45, 568B, F/UTP, Stranded, PowerCat 5e, LS0H 10m

Insert color code in place of * in part number when ordering Patch Cords: 0C=Red, 0E=Grey, 0H=Blue, 0J=Green, 0K=Yellow

MOLEX PREMISE NETWORKS

Americas Tel: 630 969 4550 www.molexpn.com **EMEA**Tel: 44 (0)2392 205800 www.molexpn.co.uk

APACTel: 61 3 9971 7111
www.molexpn.com.au