



Ledinaire Panel

RC065B LED34S/840 PSU W60L60 OC UKI

Power supply unit

The Ledinaire range contains a selection of popular off-the-shelf LED luminaires that comes with the high Philips quality levels at a competitive price. Reliable, energy efficient and affordable – just what you need.

Product data

General Information	
Beam angle of light source	– °
Light source color	840 neutral white
Light source replaceable	No
Number of gear units	1 unit
Driver/power unit/transformer	Power supply unit
Driver included	Yes
Optic type	Beam angle 90°
Luminaire light beam spread	90°
Control interface	–
Connection	Connection unit 2-pole
Cable	–
Protection class IEC	Safety class II
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	–
CE mark	CE mark
ENEC mark	–
Warranty period	3 years
Constant light output	No
Number of products on MCB of 16 A type B	35
Photobiological risk	Photobiological risk group 0 @ 200mm to EN62471
EU RoHS compliant	No
Service tag	No
Unified glare rating CEN	19
Light Technical	
Saturated Red (R9)	<50
Operating and Electrical	
Input Voltage	220 to 240 V
Input Frequency	50 or 60 Hz
Initial CLO power consumption	– W
Average CLO power consumption	– W
Inrush current	15 A
Inrush time	0.2 ms
Power Factor (Min)	0.9
Controls and Dimming	
Dimmable	No

Ledinaire Panel

Mechanical and Housing	
Housing Material	Steel
Reflector material	Acrylate
Optic material	Polystyrene
Optical cover/lens material	Polystyrene
Fixation material	-
Optical cover/lens finish	Opal
Overall length	595 mm
Overall width	595 mm
Overall height	36 mm
Color	White
Dimensions (Height x Width x Depth)	36 x 595 x 595 mm (1.4 x 23.4 x 23.4 in)

Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]

Initial Performance (IEC Compliant)	
Initial luminous flux (system flux)	3400 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	100 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>80
Initial chromaticity	(0.3818, 0.3797) SDCM≤5
Initial input power	34 W
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)	
Control gear failure rate at median useful life	7.5 %
50000 h	


Lumen maintenance at median useful life*	-
35000 h	
Lumen maintenance at median useful life*	L70
50000 h	
Lumen maintenance at median useful life*	-
75000 h	
Lumen maintenance at median useful life*	-
100000 h	

Application Conditions	
Ambient temperature range	+10 to +35 °C
Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	Not applicable

Product Data	
Full product code	871016336450699
Order product name	RC065B LED34S/840 PSU W60L60 OC UKI
EAN/UPC - Product	8710163364506
Order code	911401899880
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	911401899880
Net Weight (Piece)	2.200 kg



Dimensional drawing



Ledinaire Panel

