


Product Environmental Profile

ABR●●● Electromechanical Interface Modules





General information

Representative product

ABR Electromechanical Interface Modules -ABR1E311M

Description of the product

Control voltage: 230 V 50/60HZ, Contact: 1 C/O, 230VAC, 2 A conforming to IEC 60947-1

Description of the range

Interface according to the so-called input and output interface families.

- Narrow width
- 5 and 12 A for output interfaces
- Control LED
- 1 and 2NO/1CO/1NC+1NO contacts

The environmental impacts of this referenced product are representative of the impacts of the other products of the range which are developed with a similar technology.

Functional unit

Switch on and off during 20 years electrical power supply of a downstream installation with an electrical and/or mechanical control.

The functional unit is characterized by


Control voltage: 230 V 50/60HZ, Contact: 1 C/O, 230VAC, 2 A conforming to IEC 60947-1



Constituent materials

Reference product mass

98.187 g including the product, its packaging and additional elements and accessories



Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 8 June 2011) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers - PBDE) as mentioned in the Directive

As the products of the range are designed in accordance with the RoHS Directive (European Directive 2002/95/EC of 27 January 2003), they can be incorporated without any restriction in an assembly or an installation subject to this Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>



Additional environmental information


The ABR Electromechanical Interface Modules presents the following relevant environmental aspects

Manufacturing	Manufactured at a Schneider Electric production site ISO14001 certified		
Distribution	Weight and volume of the packaging optimized, based on the European Union's packaging directive Packaging weight is 8.1 g, consisting of cardboard (99.5%), paper (0.5%)		
Installation	Ref ABR1E311M does not require any installation operations.		
Use	The product does not require special maintenance operations.		
End of life	End of life optimized to decrease the amount of waste and allow recovery of the product components and materials No special end-of-life treatment required. According to countries' practices this product can enter the usual end-of-life treatment process. Recyclability potential: 63% Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).		

Environmental impacts

Reference life time	20 years			
Product category	Passive products - non-continuous operation			
Installation elements	No special components needed			
Use scenario	The product is in active mode 50% of the time with a power use of 3W and in stand-by mode 50% of the time with a power use of 1.5W, for 20 years			
Geographical representativeness	France			
Technological representativeness	Control voltage: 230 V 50/60HZ, Contact: 1 C/O, 230VAC, 2 A conforming to IEC 60947-1			
Energy model used	Manufacturing	Installation	Use	End of life
	Energy model used: France	Electricity grid mix; AC; consumption mix, at consumer; 230V; AT	Electricity grid mix; AC; consumption mix, at consumer; 230V; AT	Electricity grid mix; AC; consumption mix, at consumer; 230V; AT

Compulsory indicators		ABR Electromechanical Interface Modules - ABR1E311M					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	1,38E-04	7,74E-05	0*	0*	6,05E-05	0*
Contribution to the soil and water acidification	kg SO ₂ eq	3,39E-01	3,90E-03	5,78E-05	0*	3,35E-01	0*
Contribution to water eutrophication	kg PO ₄ ³⁻ eq	3,06E-02	1,37E-03	1,33E-05	0*	2,92E-02	6,89E-06
Contribution to global warming	kg CO ₂ eq	1,42E+02	5,41E-01	0*	0*	1,42E+02	0*
Contribution to ozone layer depletion	kg CFC11 eq	2,94E-07	5,44E-08	0*	6,37E-11	2,39E-07	5,77E-10
Contribution to photochemical oxidation	kg C ₂ H ₄ eq	2,35E-02	2,64E-04	4,13E-06	0*	2,32E-02	2,75E-06
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m ³	5,82E+03	0*	0*	0*	5,82E+03	0*
Total Primary Energy	MJ	3,21E+03	1,05E+01	0*	0*	3,20E+03	0*



Optional indicators		ABR Electromechanical Interface Modules - ABR1E311M						
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	
Contribution to fossil resources depletion	MJ	1,57E+03	7,70E+00	1,78E-01	0*	1,56E+03	0*	
Contribution to air pollution	m³	5,42E+03	1,83E+02	0*	0*	5,24E+03	9,20E-01	
Contribution to water pollution	m³	5,93E+03	6,22E+01	2,08E+00	0*	5,87E+03	1,07E+00	
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	
Use of secondary material	kg	9,26E-03	9,26E-03	0*	0*	0*	0*	
Total use of renewable primary energy resources	MJ	1,34E+03	3,37E-01	0*	0*	1,34E+03	0*	
Total use of non-renewable primary energy resources	MJ	1,87E+03	1,02E+01	0*	0*	1,86E+03	0*	
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	1,34E+03	3,34E-01	0*	0*	1,34E+03	0*	
Use of renewable primary energy resources used as raw material	MJ	2,97E-03	2,97E-03	0*	0*	0*	0*	
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	1,87E+03	9,20E+00	0*	0*	1,86E+03	0*	
Use of non renewable primary energy resources used as raw material	MJ	1,00E+00	1,00E+00	0*	0*	0*	0*	
Use of non renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*	
Use of renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*	
Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	
Hazardous waste disposed	kg	6,55E+00	6,14E+00	0*	1,62E-02	2,75E-01	1,20E-01	
Non hazardous waste disposed	kg	4,99E+02	3,77E-01	0*	0*	4,98E+02	0*	
Radioactive waste disposed	kg	1,20E-01	2,10E-04	0*	0*	1,19E-01	0*	
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	
Materials for recycling	kg	6,30E-02	7,73E-03	0*	0*	0*	5,52E-02	
Components for reuse	kg	0,00E+00	0*	0*	0*	0*	0*	
Materials for energy recovery	kg	1,48E-03	1,88E-04	0*	5,40E-05	0*	1,24E-03	
Exported Energy	MJ	0,00E+00	0*	0*	0*	0*	0*	

* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME© v5.6.0.1, database version 2016-11.

The use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

According to this environmental analysis, proportionality rules may be used to evaluate the impacts of other products of this range.

Depending on the impact analysis, For Contribution to mineral resources depletion, impact may be proportional extrapolated 55% by manufacturing and 45% by energy consumption. For Contribution to ozone layer depletion, impact may be proportional extrapolated 18% by manufacturing and 82% by energy consumption, the other environmental indicators of other products in this family may be proportional extrapolated by energy consumption.

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration N°	ENVPEP1704005_V1	Drafting rules	PCR-ed3-EN-2015 04 02
Date of issue	06/2017	Supplemented by	PSR-0005-ed2-EN-2016 03 29
Validity period	5 years	Information and reference	www.pep-ecopassport.org
<i>Independent verification of the declaration and data, in compliance with ISO 14025 : 2010</i>			
Internal	X	External	
<i>The elements of the present PEP cannot be compared with elements from another program.</i>			
<i>Document in compliance with ISO 14025 : 2010 « Environmental labels and declarations. Type III environmental declarations »</i>			

Schneider Electric Industries SAS

Country Customer Care Center
<http://www.schneider-electric.com/contact>

35, rue Joseph Monier
CS 30323
F- 92506 Rueil Malmaison Cedex
RCS Nanterre 954 503 439
Capital social 896 313 776 €

www.schneider-electric.com

ENVPEP1704005_V1

Published by Schneider Electric

© 2016 - Schneider Electric – All rights reserved

06/2017