



03001 (24 030 00)

MONT.SKINNE FOR MOD.PROD. G



Last ned produktdatablad for 03001



[Endre dine utvalgskriterier](#) [Produktliste](#)

[Karakteristikk](#) | [Dokumenter og nedlastning](#)

Finn andre produkter og
tilbehør



Finn ditt Schneider Electric verktøy

Teknisk informasjon



Serie	Prisma
Kompatibel med	Prisma G Prisma Pack 250
Produkt eller komponent type	Skinne
Tilbehør / separat del kategori	Installasjonstilbehør
Type festeskinne	Modulær
Installert utstyr	Multi 9: fast modular device Acti 9: fast modular device Vigirex: RH10 Vigirex: RH21 Vigirex: RH99 TeSys: fast GV2LE TeSys: fast GV2ME TeSys: fast GV2RTn Multi 9: fast modular device <= 40 A Acti 9: fast modular device <= 40 A Multi 9: fast NG125 med earth leakage protection - control: vippe Multi 9: fast NG125 uten earth leakage protection - control: vippe Multi 9: fast NG125 NA - control: vippe Acti 9: fast C120 med earth leakage protection - control: vippe Acti 9: fast C120 uten earth leakage protection - control: vippe Vigilohm: fast IM9 Vigilohm: fast IM9-OL Vigilohm: IM20 Vigilohm: IM20H Compact: fast INS40 - control: direct front rotary handle - Vertikal installasjon Compact: fast INS63 - control: direct front rotary handle - Vertikal installasjon Compact: fast INS100 - control: direct front rotary handle - Vertikal installasjon Compact: fast INS125 - control: direct front rotary handle - Vertikal installasjon Compact: fast INS160 - control: direct front rotary handle - Vertikal installasjon Acti 9: fast iC120 med earth leakage protection - control: vippe Acti 9: fast iC120 uten earth leakage protection - control: vippe Acti 9: fast 1/2 or 1 module lamp - horrisontal installasjon Acti 9: fast measurement device - horrisontal installasjon Multi 9: fast measurement device - horrisontal installasjon
Polene beskrivelse	9 x 3P: fast: GV2LE 9 x 3P: fast: GV2ME 9 x 3P: fast: GV2RTn 1 x 3P: fast: NG125 1 x 3P: fast: NG125 NA 1 x 3P: fast: C120 1 x 4P: fast: NG125 1 x 4P: fast: NG125 NA 1 x 4P: fast: C120 1 x 3P: fast: INS40 Vertikal installasjon 1 x 3P: fast: INS63 Vertikal installasjon 1 x 3P: fast: INS100 Vertikal installasjon 1 x 3P: fast: INS125 Vertikal installasjon 1 x 3P: fast: INS160 Vertikal installasjon 1 x 3P: fast: iC120 1 x 4P: fast: INS40 Vertikal installasjon 1 x 4P: fast: INS63 Vertikal installasjon 1 x 4P: fast: INS100 Vertikal installasjon 1 x 4P: fast: INS125 Vertikal installasjon 1 x 4P: fast: INS160 Vertikal installasjon 1 x 4P: fast: iC120

Komplementær



Skap/kapsling beskrivelse

Floor-standing enclosure - width 600 mm
Wall-mounted enclosure - width 600 mm
Pack enclosure - width 600 mm

Antallet vertikale moduler (50 mm)

2 module(s) : 1/2 or 1 module lamp , direct in 600 mm Wide floor-standing enclosure
2 module(s) : 1/2 or 1 module lamp , direct in 600 mm Wide wall-mounted enclosure
5 module(s) : C120 without earth leakage protection , direct in 600 mm Wide floor-standing enclosure
5 module(s) : C120 without earth leakage protection , direct in 600 mm Wide wall-mounted enclosure
3 module(s) : GV2LE , direct in 600 mm Wide floor-standing enclosure
3 module(s) : GV2LE , direct in 600 mm Wide wall-mounted enclosure
3 module(s) : GV2ME , direct in 600 mm Wide floor-standing enclosure
3 module(s) : GV2ME , direct in 600 mm Wide wall-mounted enclosure
3 module(s) : GV2RTn , direct in 600 mm Wide floor-standing enclosure
3 module(s) : GV2RTn , direct in 600 mm Wide wall-mounted enclosure
5 module(s) : iC120 without earth leakage protection , direct in 600 mm Wide floor-standing enclosure
5 module(s) : iC120 without earth leakage protection , direct in 600 mm Wide wall-mounted enclosure
3 module(s) : IM20 in 600 mm Wide floor-standing enclosure
3 module(s) : IM20 in 600 mm Wide wall-mounted enclosure
3 module(s) : IM20H in 600 mm Wide floor-standing enclosure
3 module(s) : IM20H in 600 mm Wide wall-mounted enclosure
3 module(s) : IM9 in 600 mm Wide floor-standing enclosure
3 module(s) : IM9 in 600 mm Wide wall-mounted enclosure
3 module(s) : IM9-OL in 600 mm Wide floor-standing enclosure
3 module(s) : IM9-OL in 600 mm Wide wall-mounted enclosure
4 module(s) : INS100 , direct in 600 mm Wide floor-standing enclosure
4 module(s) : INS100 , direct in 600 mm Wide wall-mounted enclosure
5 module(s) : INS100 , direct in 600 mm Wide floor-standing enclosure
5 module(s) : INS100 , direct in 600 mm Wide wall-mounted enclosure
4 module(s) : INS125 , direct in 600 mm Wide floor-standing enclosure
4 module(s) : INS125 , direct in 600 mm Wide wall-mounted enclosure
5 module(s) : INS125 , direct in 600 mm Wide floor-standing enclosure
5 module(s) : INS125 , direct in 600 mm Wide wall-mounted enclosure
4 module(s) : INS160 , direct in 600 mm Wide floor-standing enclosure
4 module(s) : INS160 , direct in 600 mm Wide wall-mounted enclosure
5 module(s) : INS160 , direct in 600 mm Wide floor-standing enclosure
5 module(s) : INS160 , direct in 600 mm Wide wall-mounted enclosure
4 module(s) : INS40 , direct in 600 mm Wide floor-standing enclosure
4 module(s) : INS40 , direct in 600 mm Wide wall-mounted enclosure
4 module(s) : INS63 , direct in 600 mm Wide floor-standing enclosure
4 module(s) : INS63 , direct in 600 mm Wide wall-mounted enclosure
2 module(s) : measurement device , direct in 600 mm Wide floor-standing enclosure
2 module(s) : measurement device , direct in 600 mm Wide wall-mounted enclosure
2 module(s) : measurement device , direct in 600 mm Wide Pack enclosure
3 module(s) : modular device <= 40 A , direct in 600 mm Wide floor-standing enclosure

	3 module(s) : RH21 , direct in 600 mm Wide wall-mounted enclosure 3 module(s) : RH99 , direct in 600 mm Wide floor-standing enclosure 3 module(s) : RH99 , direct in 600 mm Wide wall-mounted enclosure 5 module(s) : C120 with earth leakage protection , direct in 600 mm Wide floor-standing enclosure 5 module(s) : C120 with earth leakage protection , direct in 600 mm Wide wall-mounted enclosure 5 module(s) : iC120 with earth leakage protection , direct in 600 mm Wide floor-standing enclosure 5 module(s) : iC120 with earth leakage protection , direct in 600 mm Wide wall-mounted enclosure 5 module(s) : NG125 with earth leakage protection , direct in 600 mm Wide floor-standing enclosure 5 module(s) : NG125 with earth leakage protection , direct in 600 mm Wide wall-mounted enclosure
9 mm polbredde	48
Antall pr. sett	Sett á 1
Høyde	93.5 mm
Bredde	600 mm
Dybde	50 mm
Vekt	0.24 kg
Farge	Grå

Miljø  Skjul	
Standarder	IEC 61439-2 IEC 61439-1
Produktsertifikater	ASEFA

Bærekraftig  Skjul	
Bærekraftig	Green Premium produkt
RoHS (datokode: YYWW)	Compliant - since 0807 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Produktets miljøprofil	Tilgjengelig
Destruksjons-instruks	Krever ingen spesiell avfallshåndtering