



03010 (24 030 08)

MONT.SKINNE MOD.PROD. I KABELFELT G



[Last ned produktdatablad for 03010](#)



[Endre dine utvalgskriterier](#) [Produktliste](#)

Finn andre produkter og
tilbehør



Finn ditt Schneider Electric verktøy

[Karakteristikk](#) | [Dokumenter og nedlastning](#)

Teknisk informasjon



Serie	Prisma
Kompatibel med	Prisma G
Produkt eller komponent type	Skinne
Tilbehør / separat del kategori	Installasjonstilbehør
Type festeskinne	Modulær
Installert utstyr	Multi 9: fast modular device Acti 9: fast modular device TeSys: fast GV2LE TeSys: fast GV2ME TeSys: fast GV2RTn Multi 9: fast modular device <= 40 A Acti 9: fast modular device <= 40 A Multi 9: fast NG125 med earth leakage protection - control: vippe Multi 9: fast NG125 uten earth leakage protection - control: vippe Multi 9: fast NG125 NA - control: vippe Acti 9: fast C120 med earth leakage protection - control: vippe Acti 9: fast C120 uten earth leakage protection - control: vippe Compact: fast INS40 - control: direct front rotary handle - Vertikal installasjon Compact: fast INS63 - control: direct front rotary handle - Vertikal installasjon Compact: fast INS100 - control: direct front rotary handle - Vertikal installasjon Compact: fast INS125 - control: direct front rotary handle - Vertikal installasjon Compact: fast INS160 - control: direct front rotary handle - Vertikal installasjon Acti 9: fast iC120 med earth leakage protection - control: vippe Acti 9: fast iC120 uten earth leakage protection - control: vippe
Polene beskrivelse	1 x 3P: fast: NG125 1 x 3P: fast: NG125 NA 1 x 3P: fast: C120 1 x 4P: fast: NG125 1 x 4P: fast: NG125 NA 1 x 4P: fast: C120 1 x 3P: fast: INS40 Vertikal installasjon 1 x 3P: fast: INS63 Vertikal installasjon 1 x 3P: fast: INS100 Vertikal installasjon 1 x 3P: fast: INS125 Vertikal installasjon 1 x 3P: fast: INS160 Vertikal installasjon 1 x 3P: fast: iC120 1 x 4P: fast: INS40 Vertikal installasjon 1 x 4P: fast: INS63 Vertikal installasjon 1 x 4P: fast: INS100 Vertikal installasjon 1 x 4P: fast: INS125 Vertikal installasjon 1 x 4P: fast: INS160 Vertikal installasjon 1 x 4P: fast: iC120 4 x 3P: fast: GV2LE 4 x 3P: fast: GV2ME 4 x 3P: fast: GV2RTn

Komplementær



Skap/kapsling beskrivelse	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm
Antallet vertikale moduler (50 mm)	4 module(s) : C120 without earth leakage protection , direct in 300 mm Wide floor-standing duct 4 module(s) : C120 without earth leakage protection , direct in 300 mm Wide wall-mounted duct 3 module(s) : GV2LE , direct in 300 mm Wide floor-standing duct 3 module(s) : GV2LE , direct in 300 mm Wide wall-mounted duct 3 module(s) : GV2ME , direct in 300 mm Wide floor-standing duct 3 module(s) : GV2ME , direct in 300 mm Wide wall-mounted duct 3 module(s) : GV2RTn , direct in 300 mm Wide floor-standing duct 3 module(s) : GV2RTn , direct in 300 mm Wide wall-mounted duct 4 module(s) : iC120 without earth leakage protection , direct in 300 mm Wide floor-standing duct

	4 module(s) : iC120 without earth leakage protection , direct in 300 mm Wide wall-mounted duct 4 module(s) : INS100 , direct in 300 mm Wide floor-standing duct 4 module(s) : INS100 , direct in 300 mm Wide wall-mounted duct 5 module(s) : INS100 , direct in 300 mm Wide floor-standing duct 5 module(s) : INS100 , direct in 300 mm Wide wall-mounted duct 4 module(s) : INS125 , direct in 300 mm Wide floor-standing duct 4 module(s) : INS125 , direct in 300 mm Wide wall-mounted duct 5 module(s) : INS125 , direct in 300 mm Wide floor-standing duct 5 module(s) : INS125 , direct in 300 mm Wide wall-mounted duct 4 module(s) : INS160 , direct in 300 mm Wide floor-standing duct 4 module(s) : INS160 , direct in 300 mm Wide wall-mounted duct 5 module(s) : INS160 , direct in 300 mm Wide floor-standing duct 5 module(s) : INS160 , direct in 300 mm Wide wall-mounted duct 4 module(s) : INS40 , direct in 300 mm Wide floor-standing duct 4 module(s) : INS40 , direct in 300 mm Wide wall-mounted duct 4 module(s) : INS63 , direct in 300 mm Wide floor-standing duct 4 module(s) : INS63 , direct in 300 mm Wide wall-mounted duct 3 module(s) : modular device <= 40 A , direct in 300 mm Wide floor-standing duct 3 module(s) : modular device <= 40 A , direct in 300 mm Wide wall-mounted duct 4 module(s) : modular device , direct in 300 mm Wide floor-standing duct 4 module(s) : modular device , direct in 300 mm Wide wall-mounted duct 4 module(s) : NG125 without earth leakage protection , direct in 300 mm Wide floor-standing duct 4 module(s) : NG125 without earth leakage protection , direct in 300 mm Wide wall-mounted duct 4 module(s) : NG125 NA , direct in 300 mm Wide floor-standing duct 4 module(s) : NG125 NA , direct in 300 mm Wide wall-mounted duct 4 module(s) : C120 with earth leakage protection , direct in 300 mm Wide floor-standing duct 4 module(s) : C120 with earth leakage protection , direct in 300 mm Wide wall-mounted duct 4 module(s) : iC120 with earth leakage protection , direct in 300 mm Wide floor-standing duct 4 module(s) : iC120 with earth leakage protection , direct in 300 mm Wide wall-mounted duct 4 module(s) : NG125 with earth leakage protection , direct in 300 mm Wide floor-standing duct 4 module(s) : NG125 with earth leakage protection , direct in 300 mm Wide wall-mounted duct
9 mm polbredde	20
Antall pr. sett	Sett á 1
Høyde	93.5 mm
Bredde	300 mm
Dybde	50 mm
Vekt	0.14 kg
Farge	Grå
Materiale	Metall

Miljø 	
Standarder	IEC 61439-2 IEC 61439-1
Produktsertifikater	ASEFA

Bærekraftig 	
Bærekraftig	Green Premium produkt
RoHS (datokode: YYWW)	Compliant - since 0807 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Produktets miljøprofil	Tilgjengelig

