



03032 (24 030 12)

MONT.PL NS250 HOR. MT FAST/MAN. PL.INN



Last ned produktdatablad for 03032



[Endre dine utvalgsriterier](#) [Produktliste](#)

[Karakteristikk](#) | [Dokumenter og nedlastning](#)

Finn andre produkter og
tilbehør



Finn ditt Schneider Electric verktøy

Teknisk informasjon



Serie	Prisma
Kompatibel med	Prisma G
Produkt eller komponent type	Montasjeplate
Tilbehør / separat del kategori	Installasjonstilbehør
Installert utstyr	Compact: fast NSX100...160 uten earth leakage protection - control: motormekanisme - horrisontal installasjon Compact: fast NSX250 uten earth leakage protection - control: motormekanisme - horrisontal installasjon Compact: plugg inn NSX100...160 uten earth leakage protection - control: vippe - horrisontal installasjon Compact: plugg inn NSX250 uten earth leakage protection - control: vippe - horrisontal installasjon Compact: fast INS250 - control: lateral handle - Vertikal installasjon Compact: fast INV250 - control: lateral handle - Vertikal installasjon
Polene beskrivelse	1 x 3P: fast: NSX100...160 horrisontal installasjon 1 x 4P: fast: NSX100...160 horrisontal installasjon 1 x 3P: fast: NSX250 horrisontal installasjon 1 x 4P: fast: NSX250 horrisontal installasjon 1 x 3P: plugg inn: NSX100...160 horrisontal installasjon 1 x 3P: plugg inn: NSX250 horrisontal installasjon 1 x 3P: fast: INS250 Vertikal installasjon 1 x 3P: fast: INV250 Vertikal installasjon 1 x 4P: plugg inn: NSX100...160 horrisontal installasjon 1 x 4P: plugg inn: NSX250 horrisontal installasjon 1 x 4P: fast: INS250 Vertikal installasjon 1 x 4P: fast: INV250 Vertikal installasjon

Komplementær



Skap/kapsling beskrivelse	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Floor-standing enclosure + duct - width 600 + 300 mm Wall-mounted enclosure + duct - width 600 + 300 mm
Antallet vertikale moduler (50 mm)	4 module(s) : NSX100...160 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming from top or bottom of enclosure) 4 module(s) : NSX100...160 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide wall-mounted enclosure + duct (cable coming from top or bottom of enclosure) 4 module(s) : NSX250 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide floor-standing enclosure + duct (cable coming from top or bottom of enclosure) 4 module(s) : NSX250 without earth leakage protection , direct with long terminal shield in 600 + 300 mm Wide wall-mounted enclosure + duct (cable coming from top or bottom of enclosure) 8 module(s) : INS250, direct with long terminal shield in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 8 module(s) : INS250, direct with long terminal shield in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure) 8 module(s) : INV250, direct with long terminal shield in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 8 module(s) : INV250, direct with long terminal shield in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure)
Betingelse for bruken	Need additional plate (2M high) when installation of device is in horizontal Need additional plate (1M high) when installation of device is in vertical
Høyde	150 mm
Vekt	0.96 kg
Type overflate	Matt Glatt

Overflatebeskyttelse	Elektroforese behandling og hot-polymerisert polyester epoxy pulver
Farge	Hvit RAL 9001

Miljø  Skjul	
Standarder	IEC 61439-2
Produktsertifikater	ASEFA

Bærekraftig  Skjul	
Bærekraftig	Green Premium produkt
RoHS (datokode: YYWW)	Compliant - since 0807 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Produktets miljøprofil	Tilgjengelig
Destruksjons-instruks	Krever ingen spesiell avfallshåndtering