



03043 (24 030 16)

MONT.PL MAN.OMKOPLER NS-INS 100-250 G



[Last ned produktdatablad for 03043](#)



[Endre dine utvalgskriterier](#) [Produktliste](#)

Finn andre produkter og
tilbehør



Finn ditt Schneider Electric verktøy

[Karakteristikk](#) | [Dokumenter og nedlastning](#)

Teknisk informasjon

[Skjul](#)

Serie	Prisma
Kompatibel med	Prisma G
Produkt eller komponent type	Montasjeplate
Tilbehør / separat del kategori	Installasjonstilbehør
Installert utstyr	Compact: fast INS250 source changeover - control: mekanisk forigling - Vertikal installasjon Compact: fast INV250 source changeover - control: mekanisk forigling - Vertikal installasjon Compact: fast INS250 source changeover - control: direct front rotary handle - Vertikal installasjon Source changeover: fast NSX100...250 source changeover - control: mekanisk forigling - Vertikal installasjon
Polene beskrivelse	1 x 3P: fast: NSX100...250 source changeover Vertikal installasjon 1 x 3P: fast: INS250 source changeover Vertikal installasjon 1 x 3P: fast: INV250 source changeover Vertikal installasjon 1 x 4P: fast: NSX100...250 source changeover Vertikal installasjon 1 x 4P: fast: INS250 source changeover Vertikal installasjon 1 x 4P: fast: INV250 source changeover Vertikal installasjon

Komplementær

[Skjul](#)

Skap/kapsling beskrivelse	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm
Antallet vertikale moduler (50 mm)	10 module(s) : INS250 source changeover, front connection in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 10 module(s) : INS250 source changeover, front connection in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure) 10 module(s) : INV250 source changeover, front connection in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 10 module(s) : INV250 source changeover, front connection in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure) 11 module(s) : NSX100...250 source changeover, front connection in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 11 module(s) : NSX100...250 source changeover, front connection in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure)
Betingelse for bruken	Need additional plate (1M high) when installation of device is in vertical
Høyde	200 mm
Vekt	1.37 kg
Type overflate	Matt Glatt
Overflatebeskyttelse	Elektroforese behandling og hot-polymerisert polyester epoxy pulver
Farge	Hvit RAL 9001

Miljø

[Skjul](#)

Standarder	IEC 61439-2
Produktsertifikater	ASEFA

Bærekraftig

[Skjul](#)

Bærekraftig	Green Premium produkt
RoHS (datokode: YYWW)	Compliant - since 0807 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Produktets miljøprofil	Tilgjengelig
Destruksjons-instruks	Krever ingen spesiell avfallshåndtering