



03051 (24 030 18)

MONT.PL NS100-250 DREIEH. KABELFELT G



[Last ned produktdatablad for 03051](#)



[Endre dine utvalgskriterier](#) [Produktliste](#)

Finn andre produkter og
tilbehør



Finn ditt Schneider Electric verktøy

[Karakteristikk](#) | [Dokumenter og nedlastning](#)

Teknisk informasjon

[Skjul](#)

Serie	Prisma
Kompatibel med	Prisma P Prisma G
Produkt eller komponent type	Montasjeplate
Tilbehør / separat del kategori	Installasjonstilbehør
Installert utstyr	Compact: fast NSX100...160 uten earth leakage protection - control: direct front rotary handle - Vertikal installasjon Compact: fast NSX250 uten earth leakage protection - control: direct front rotary handle - Vertikal installasjon Compact: plugg inn NSX100...160 uten earth leakage protection - control: direct front rotary handle - Vertikal installasjon Compact: plugg inn NSX250 uten earth leakage protection - control: direct front rotary handle - Vertikal installasjon Compact: fast NSX100...160 uten earth leakage protection - control: motormekanisme - Vertikal installasjon Compact: fast NSX250 uten earth leakage protection - control: motormekanisme - Vertikal installasjon Compact: plugg inn NSX100...160 uten earth leakage protection - control: motormekanisme - Vertikal installasjon Compact: plugg inn NSX250 uten earth leakage protection - control: motormekanisme - Vertikal installasjon Easypact: fast CVS100...160 uten earth leakage protection - control: direct front rotary handle - Vertikal installasjon Easypact: fast CVS250 uten earth leakage protection - control: direct front rotary handle - Vertikal installasjon
Polene beskrivelse	1 x 3P: fast: NSX100...160 Vertikal installasjon 1 x 3P: fast: NSX250 Vertikal installasjon 1 x 3P: fast: CVS100...160 Vertikal installasjon 1 x 3P: fast: CVS250 Vertikal installasjon 1 x 4P: fast: NSX100...160 Vertikal installasjon 1 x 4P: fast: NSX250 Vertikal installasjon 1 x 4P: fast: CVS100...160 Vertikal installasjon 1 x 4P: fast: CVS250 Vertikal installasjon 1 x 3P: plugg inn: NSX100...160 Vertikal installasjon 1 x 3P: plugg inn: NSX250 Vertikal installasjon 1 x 4P: plugg inn: NSX250 Vertikal installasjon 1 x 4P: plugg inn: NSX100...160 Vertikal installasjon

Komplementær

[Skjul](#)

Skap/kapsling beskrivelse	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm Cubicle - width 400 mm, depth 400 mm
Antallet vertikale moduler (50 mm)	9 module(s) : CVS100...160 without earth leakage protection , direct with long terminal shield in 300 mm Wide floor-standing duct (cable coming from top or bottom of enclosure) 9 module(s) : CVS100...160 without earth leakage protection , direct with long terminal shield in 300 mm Wide wall-mounted duct (cable coming from top or bottom of enclosure) 9 module(s) : CVS250 without earth leakage protection , direct with long terminal shield in 300 mm Wide floor-standing duct (cable coming from top or bottom of enclosure) 9 module(s) : CVS250 without earth leakage protection , direct with long terminal shield in 300 mm Wide wall-mounted duct (cable coming from top or bottom of enclosure) 9 module(s) : NSX100...160 without earth leakage protection , direct with long terminal shield in 300 mm Wide floor-standing duct (cable coming from top or bottom of enclosure) 9 module(s) : NSX100...160 without earth leakage protection , direct with long terminal shield in 300 mm Wide wall-mounted duct (cable coming from top or bottom of enclosure) 9 module(s) : NSX100...160 without earth leakage protection , front connection in 400 mm Wide cubicle 9 module(s) : NSX250 without earth leakage protection , direct with long terminal shield in 300 mm Wide floor-standing duct (cable coming from top or bottom of enclosure) 9 module(s) : NSX250 without earth leakage protection , direct with long terminal shield in 300 mm Wide wall-mounted duct (cable coming

	from top or bottom of enclosure) 9 module(s) : NSX250 without earth leakage protection , front connection in 400 mm Wide cubicle
Betingelse for bruken	Need additional plate (1M high) when installation of device is in vertical
Høyde	300 mm
Vekt	0.5 kg
Type overflate	Matt Glatt
Overflatebeskyttelse	Elektroforese behandling og hot-polymerisert polyester epoxy pulver
Farge	Hvit RAL 9001

Miljø

 Skjul

Standarder	IEC 61439-2
Produktsertifikater	ASEFA

Bærekraftig

 Skjul

Bærekraftig	Green Premium produkt
RoHS (datokode: YYWW)	Compliant - since 0807 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Produktets miljøprofil	Tilgjengelig
Destruksjons-instruks	Krever ingen spesiell avfallshåndtering