



03074 (24 030 21)

MONT.PLATE NS400-630 VERT. DREIEH. G



[Last ned produktdatablad for 03074](#)



[Endre dine utvalgskriterier](#) [Produktliste](#)

Finn andre produkter og
tilbehør



Finn ditt Schneider Electric verktøy

[Karakteristikk](#) | [Dokumenter og nedlastning](#)

Teknisk informasjon

[Skjul](#)

Serie	Prisma
Kompatibel med	Prisma G
Produkt eller komponent type	Montasjeplate
Tilbehør / separat del kategori	Installasjonstilbehør
Installert utstyr	Compact: fast NSX400 uten earth leakage protection - control: direct front rotary handle - Vertikal installasjon Compact: fast NSX630 uten earth leakage protection - control: direct front rotary handle - Vertikal installasjon Easypact: fast CVS400 uten earth leakage protection - control: direct front rotary handle - Vertikal installasjon Easypact: fast CVS630 uten earth leakage protection - control: direct front rotary handle - Vertikal installasjon Compact: fast NSX400 med earth leakage protection - control: direct front rotary handle - Vertikal installasjon Compact: fast NSX630 med earth leakage protection - control: direct front rotary handle - Vertikal installasjon Easypact: fast CVS400 med earth leakage protection - control: direct front rotary handle - Vertikal installasjon Easypact: fast CVS630 med earth leakage protection - control: direct front rotary handle - Vertikal installasjon
Polene beskrivelse	1 x 3P: fast: NSX400 Vertikal installasjon 1 x 3P: fast: NSX630 Vertikal installasjon 1 x 3P: fast: CVS400 Vertikal installasjon 1 x 3P: fast: CVS630 Vertikal installasjon 1 x 4P: fast: NSX400 Vertikal installasjon 1 x 4P: fast: NSX630 Vertikal installasjon 1 x 4P: fast: CVS400 Vertikal installasjon 1 x 4P: fast: CVS630 Vertikal installasjon

Komplementær

[Skjul](#)

Skap/kapsling beskrivelse	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm
Antallet vertikale moduler (50 mm)	15 module(s) : CVS400 without earth leakage protection , direct with long terminal shield in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 15 module(s) : CVS400 without earth leakage protection , direct with long terminal shield in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure) 15 module(s) : CVS630 without earth leakage protection , direct with long terminal shield in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 15 module(s) : CVS630 without earth leakage protection , direct with long terminal shield in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure) 15 module(s) : NSX400 without earth leakage protection , direct with long terminal shield in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 15 module(s) : NSX400 without earth leakage protection , direct with long terminal shield in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure) 15 module(s) : NSX630 without earth leakage protection , direct with long terminal shield in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 15 module(s) : NSX630 without earth leakage protection , direct with long terminal shield in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure) 18 module(s) : CVS400 with earth leakage protection , direct with long terminal shield in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 18 module(s) : CVS400 with earth leakage protection , direct with long terminal shield in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure) 18 module(s) : CVS630 with earth leakage protection , direct with long terminal shield in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 18 module(s) : CVS630 with earth leakage protection , direct with long terminal shield in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure)

	from top or bottom of enclosure) 18 module(s) : NSX400 with earth leakage protection , direct with long terminal shield in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 18 module(s) : NSX400 with earth leakage protection , direct with long terminal shield in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure) 18 module(s) : NSX630 with earth leakage protection , direct with long terminal shield in 600 mm Wide floor-standing enclosure (cable coming from top or bottom of enclosure) 18 module(s) : NSX630 with earth leakage protection , direct with long terminal shield in 600 mm Wide wall-mounted enclosure (cable coming from top or bottom of enclosure)
Betingelse for bruken	Need additional plate (1M high) when installation of device is in vertical
Høyde	500 mm
Vekt	2.24 kg
Type overflate	Matt Glatt
Overflatebeskyttelse	Elektroforese behandling og hot-polymerisert polyester epoxy pulver
Farge	Hvit RAL 9001

Miljø

 Skjul

Standarder	IEC 61439-2
Produktsertifikater	ASEFA

Bærekraftig

 Skjul

Bærekraftig	Green Premium produkt
RoHS (datokode: YYWW)	Compliant - since 0807 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Produktets miljøprofil	Tilgjengelig
Destruksjons-instruks	Krever ingen spesiell avfallshåndtering