



03214 (24 030 73)

FRONTPL. 4M MOD.PROD. KABELFELT G



[Last ned produktdatablad for 03214](#)



[Endre dine utvalgsriterier](#) [Produktliste](#)

Finn andre produkter og
tilbehør



Finn ditt Schneider Electric verktøy

[Karakteristikk](#) | [Dokumenter og nedlastning](#)

Teknisk informasjon



Serie	Prisma
Kompatibel med	Prisma P Prisma G
Produkt eller komponent type	Front plate
Tilbehør / separat del kategori	Installasjonstilbehør
Type frontplate	Modul Skjære ut
Installert utstyr	Multi 9: fast modular device Acti 9: fast modular device Multi 9: fast NG125 med earth leakage protection - control: vippe Multi 9: fast NG125 uten earth leakage protection - control: vippe Multi 9: fast NG125 NA - control: vippe Acti 9: fast C120 med earth leakage protection - control: vippe Acti 9: fast C120 uten earth leakage protection - control: vippe Compact: fast NG160 uten earth leakage protection - control: vippe Compact: fast NSA125...160 - control: vippe Compact: fast INS40 - control: direct front rotary handle - Vertikal installasjon Compact: fast INS63 - control: direct front rotary handle - Vertikal installasjon Compact: fast INS100 - control: direct front rotary handle - Vertikal installasjon Compact: fast INS125 - control: direct front rotary handle - Vertikal installasjon Compact: fast INS160 - control: direct front rotary handle - Vertikal installasjon Compact: fast NG160 NA uten earth leakage protection - control: vippe Acti 9: fast iC120 med earth leakage protection - control: vippe Acti 9: fast iC120 uten earth leakage protection - control: vippe Compact : fixed NSXm without earth leakage protection - control: toggle - vertical installation Compact : fixed NSXm with earth leakage protection - control: toggle - vertical installation
Polene beskrivelse	1 x 3P: modular rail support: INS100 Vertikal installasjon 1 x 4P: modular rail support: INS100 Vertikal installasjon 1 x 3P: modular rail support: INS125 Vertikal installasjon 1 x 4P: modular rail support: INS125 Vertikal installasjon 1 x 3P: modular rail support: INS160 Vertikal installasjon 1 x 4P: modular rail support: INS160 Vertikal installasjon 1 x 3P: modular rail support: INS40 Vertikal installasjon 1 x 4P: modular rail support: INS40 Vertikal installasjon 1 x 3P: modular rail support: INS63 Vertikal installasjon 1 x 4P: modular rail support: INS63 Vertikal installasjon 1 x 3P: modular rail support: C120 1 x 4P: modular rail support: C120 1 x 3P: modular rail support: iC120 1 x 4P: modular rail support: iC120 1 x 3P: modular rail support: NG125 1 x 4P: modular rail support: NG125 1 x 3P: modular rail support: NG125 NA 1 x 4P: modular rail support: NG125 NA 1 x 3P: modular rail support: NG160 1 x 4P: modular rail support: NG160 1 x 3P: modular rail support: NG160 NA 1 x 4P: modular rail support: NG160 NA 1 x 3P: modular rail support: NSA125...160 1 x 4P: modular rail support: NSA125...160 1 x 3P or 4P : modular rail support : NSXm vertical installation
Driftsposisjon	Vertikal

Komplementær



Skap/kapsling beskrivelse	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm Cubicle - width 400 mm, depth 400 mm
Posisjon for tilkobling	Direkte/bolt tilkobling

9 mm polbredde	20
Antall 18 mm moduller per rad	10
Antall vertikale moduler	4
Standarder	IEC 61439-2 IEC 61439-1
Produktsertifikater	ASEFA
Antall pr. sett	Sett á 1
Høyde	200 mm
Bredde	300 mm
Vekt	0.4 kg
Materiale	Stål
Type overflate	Matt Glatt
Overflatebeskyttelse	Elektroforese behandling og hot-polymerisert polyester epoxy pulver
Farge	Hvit RAL 9001

Miljø Skjul

IK beskyttelsesklasse IK07 i samsvar med EN/IEC 62262

Bærekraftig Skjul

Bærekraftig Green Premium produkt

RoHS (datokode: YYWW) Compliant - since 0701 - Schneider Electric declaration of conformity

REACH Reference not containing SVHC above the threshold

Produktets miljøprofil Tilgjengelig

Destruksjons-instruks Krever ingen spesiell avfallshåndtering