



04064 (24 033 42)

TILKOPL.KLEMME NS/INS250 P.C. KABELF. G



[Last ned produktdatablad for 04064](#)



[Endre dine utvalgskriterier](#) [Produktliste](#)

Finn andre produkter og
tilbehør



Finn ditt Schneider Electric verktøy

[Karakteristikk](#) | [Dokumenter og nedlastning](#)

Teknisk informasjon

[Skjul](#)

Serie	Linergy
Produkt navn	Linergy BW
Produkt eller komponent type	Forbindelse
Tilbehør / separat del kategori	Strømfordelingstilbehør

Komplementær

[Skjul](#)

Skap - utstyrsilkobling	Linergy BW universal power supply block
Antall poler	4P
Skap/kapsling beskrivelse	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm Cubicle duct - width 300 mm
Installert utstyr	Compact: fast INS250 - control: direct front rotary handle Vertikal installasjon Compact: fast INV250 - control: direct front rotary handle Vertikal installasjon Easypact: fast CVS100...160 uten earth leakage protection - control: direct front rotary handle Vertikal installasjon Easypact: fast CVS250 uten earth leakage protection - control: direct front rotary handle Vertikal installasjon Easypact: fast CVS100...160 uten earth leakage protection - control: vippe Vertikal installasjon Easypact: fast CVS250 uten earth leakage protection - control: vippe Vertikal installasjon Compact: fast INV100 - control: direct front rotary handle Vertikal installasjon Compact: fast NSX100...160 uten earth leakage protection - control: vippe Vertikal installasjon Compact: fast NSX250 uten earth leakage protection - control: vippe Vertikal installasjon Compact: fast NSX100...160 uten earth leakage protection - control: direct front rotary handle Vertikal installasjon Compact: fast NSX250 uten earth leakage protection - control: direct front rotary handle Vertikal installasjon Compact: fast INV200 - control: direct front rotary handle Vertikal installasjon Compact : fixed INV160 - control: direct front rotary handle vertical installation
[Ie] nominell driftsstrøm	250 A
Antall pr. sett	Sett á 4
Vekt	2.72 kg
Farge	Antrasitt grå RAL 7016

Miljø

[Skjul](#)

Standarder	IEC 61439-1, inside Prisma IEC 61439-2, inside Prisma
Produktsertifikater	ASEFA

Bærekraftig

[Skjul](#)

Bærekraftig	Green Premium produkt
RoHS (datokode: YYWW)	Compliant - since 0707 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Produktets miljøprofil	Tilgjengelig
Destruksjons-instruks	Krever ingen spesiell avfallshåndtering

