



56293 (16 099 15)

Jordfeilrele Vigirex RH99P 220/240V AC automatisk reset

[Last ned produktdatablad for 56293](#)[Endre dine utvalgskriterier](#) [Produktliste](#)[Finn andre produkter og tilbehør](#)[Finn ditt Schneider Electric verktøy](#)[Karakteristikk](#) | [Dokumenter og nedlastning](#)

Teknisk informasjon

 Skjul

Serie	Vigirex
Produktspekter	Vigirex
Kortnavn utstyr	RH99P
Produkt eller komponent type	Residual current protection relay
Kompatibel med	Vigirex Vigirex RH TOA earth leakage current sensor Vigirex Vigirex RH A earth leakage current sensor
Relefunksjon	Rele med automatisk reset

Komplementær

 Skjul

Jordingssystem	TN-S TT
[Us] matespenning	220...240 V AC at 400 Hz 55...110 % 220...240 V AC at 50/60 Hz 55...110 %
Effektforbruk	4 VA
Type måling	Earth fault current internal measurement 80...100 %
Innstillingsgrense	0.03...30 A alarm
Tidsforsinker innstilling	Adjustable 9 settings 0.1...30 A 0...4.5 s Momentan 0.03...30 A
Test funksjon	Lokal Fjern test
Overvåking	Electronics (continuous) Strømforsyning (continuous) Relay/sensor link (continuous)
[Ithe] konvensjonell kapslet termisk strøm	8 A
Minimum belastning	10 mA på 12 V
Vekt	0.3 kg
Mekanisk robusthet	Fire resistance i samsvar med IEC 60695-2-1 Vibrations 13.2...100 Hz: 0.7 g Vibrations 2...13.2 Hz: +/- 1 mm
Jordfeilvern klasse	Klasse A si Klasse AC
Overspenningskategori	IV
Manipuleringsikre instillinger	Beskyttet med forseglbart deksel
Montering	Panel
Høyde	72 mm
Bredde	72 mm
Dybde	78 mm
Tilkoblingsklemmer	Terminal block auxiliary power supply 0.2...2.5 mm² flexible AWG 24...AWG 12 Terminal block auxiliary power supply 0.2...2.5 mm² rigid AWG 24...AWG 12 Terminal block auxiliary power supply 0.25...2.5 mm² flexible with ferrule AWG 24...AWG 12 Terminal block fault 0.2...2.5 mm² flexible AWG 24...AWG 12 Terminal block fault 0.2...2.5 mm² rigid AWG 24...AWG 12 Terminal block fault 0.25...2.5 mm² flexible with ferrule AWG 24...AWG 12 Terminal block relay test and fault reset 0.2...2.5 mm² flexible AWG 24...AWG 12 Terminal block relay test and fault reset 0.2...2.5 mm² rigid AWG 24...AWG 12 Terminal block relay test and fault reset 0.25...2.5 mm² flexible with ferrule AWG 24...AWG 12 Terminal block sensor 0.2...2.5 mm² flexible AWG 24...AWG 12

	Terminal block sensor 0.2...2.5 mm² rigid AWG 24...AWG 12 Terminal block sensor 0.25...2.5 mm² flexible with ferrule AWG 24...AWG 12 Terminal block voltage presence 0.2...2.5 mm² flexible AWG 24...AWG 12 Terminal block voltage presence 0.2...2.5 mm² rigid AWG 24...AWG 12 Terminal block voltage presence 0.25...2.5 mm² flexible with ferrule AWG 24...AWG 12
Avmantlings lengde	FAULT: 7 mm Sensor: 7 mm Voltage presence: 7 mm Auxiliary power supply: 7 mm Relay test and fault reset: 7 mm
Tiltrekningsmoment	Auxiliary power supply: 0.6 N.m FAULT: 0.6 N.m Relay test and fault reset: 0.6 N.m Sensor: 0.6 N.m Voltage presence: 0.6 N.m

Miljø

 Skjul

Omgivelsestemperatur drift	-35...70 °C
Omgivelsestemperatur for lagring	-55...85 °C
Elektromagnetisk kompatibilitet	Gjennomført og utstrålt emisjon: B i samsvar med CISPR 11 Conducted radio-frequency immunity test: 3 i samsvar med IEC 61000-4-6 Immunitetstest for elektrostatisk utladning: 4 i samsvar med IEC 61000-4-2 High-energy conducted susceptibility: 4 i samsvar med IEC 61000-4-5 Low-energy conducted susceptibility: 4 i samsvar med IEC 61000-4-4 Radiated susceptibility: 3 i samsvar med IEC 61000-4-3
Beskyttelsesgrad mot elektrisk støt	Klasse II