



Oversikt

Leveringstid	Usually in Stock
--------------	------------------

Generelt

Inkludert utstyr	1 x detachable IEC power cord Telephone cable Brukermanual USB kabel
Prestanda multiplikator	1
Number of tare power	30 W
Number of power module free slots	0
Number of power module filled slots	0
Overflødig	No
Size UPS version	Workstation
UPS størrelse	WS
Verdimultiplikator	1

Fysisk

Farge	Sort
Dybde	38 cm
Høyde	30,1 cm
Mounting preference	No preference
Vekt	12,7 kg
Monteringsmetode	Not rack-mountable
Two post mountable	0
USB kompatibel	No
Bredde	11,2 cm

Input

Nettverksfrekvens	50/60 Hz +/- 3 Hz automatisk gjenkjenning
Plugg standard	IEC 60320 C14
Toleranse forsyningsspenning	156...300 V Justrbar 176...294 V
Brytekapasitet, A	10 A
Antall kabler	1
Forsyningsspenning	230 V

Output

Merkeeffekt i W	865 W
Maximum configurable power in W	865 W
Utgangsfrekvens	50/60 Hz +/- 3 Hz sync to mains
Crest faktor	3:1
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Nb of power socket outlets	5 IEC 60320 C13 5 IEC 60320 C13 surge 2 IEC Jumpers
Curve equation	Efficiency
Curve fixed loss	0,0086
Maksimal kurvebelastning	100 %
Minimums kurvebelastning	1 %
Curve proportional loss	0
Curve square loss	0,0023
Kurve X-aksel maksimum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 230V/50Hz electrical input and balanced resistive load (PF =
Kurve X-akse minimum	0 %
Kurve X-akse tittel	Load
Kurve X-akse enheter	Percentage
Kurve Y-akse maksimum	100 %
Kurve Y-akse minimum	50 %
Kurve Y-akse tittel	Efficiency
Kurve Y-akse enheter	Percentage
Grafvisning	1
Utgangsspenning	230 V
Maximum configurable power in VA	1500 VA
Merkeeffekt VA	1500 VA
Overføringstid	10 ms typical : 12 ms maximum

Overenstemmelse

Produktsertifikater	A-Tick C-Tick CE GOST Telepermit TÜV
Merking	GS Mark
Equipment protection policy	Lifetime : 200000 AUD Lifetime : 150000 euros Lifetime : 75000 GBP

Miljømessig

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 %
Driftshøyde	0...30000 ft
Omgivelsestemperatur for lagring	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0,00...15240,00 m
Akkustikknivå	45 dBA
Show note OP temperature	No

Batteri og levetid

Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 t
Number of battery replacement quantity	1
Liquid value	0
Batterispenningen	24 V
Kapasitet på batteri	9,0 Ah
Betterikurve	C
Batteri ladekraft	23 W rated
Batterikraft i VAh	216 VAh capacity 187 VAh runtime
Batterilevetid	3...5 år
Batteri alternativ	BR24BP 1 518 VAh BR24BPG 1 518 VAh
Kommentarer om batteridiagram	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v
Extended runtime	0

Kommunikasjon og ledelse

Kontrollpanel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Overspenningsbeskyttelse og filtrering

Surge energy rate	441 J
Noise suppression	Full time multi-pole noise filtering : 10% of IEEE surge let-through : zero clamping response time: instantaneous
Data line protection	RJ11 analog phone line for phone/fax/modem/DSL RJ45 network line - 10/100/1000 Base-T Ethernet

Forpakkingsinformasjon

Forpakning 1 vekt	14,3 kg
Forpakning 1 høyde	38,7 cm
Forpakning 1 bredde	23,8 cm
Forpakning 1 lengde	48,8 cm
SCC14	10731304268748
Antall enheter forpakning 2	1
Antall enheter forpakning 3	20

Bærekraftig

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Miljøinformasjon	 Produktmiljøprofil
Produktets livssyklus	 Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available

Garantiperiode

Garanti	2 years repair or replace, 3 years repair or replace for European Union countries
---------	---