



Oversikt

Presentasjon	APC Metered Rack Power Distribution Units (PDUs) provide active metering to enable energy optimization and circuit protection. The output and input connections are (36) C13 & (6) C19, and the cable length is 3m. User-defined alarm thresholds mitigate risk with real-time local and remote alerts to warn of potential circuit overloads. Metered Rack PDUs provide power utilization data to allow Data Center Managers to make informed decisions on load balancing and right sizing IT environments to lower the total cost of ownership. Metered Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and ultra-low profile circuit breakers. Users can access and configure Metered Rack PDUs through secure Web, SNMP, or Telnet Interfaces which are complimented by APC Centralized Management platforms using InfraStruxure Central, Operations, Capacity, and Energy Efficiency.
Leveringstid	Usually in Stock

Generelt

Tilgjengelig utstyr	Installation guide Rack mounting brackets Serial configuration cable Safety guide
---------------------	--

Fysisk

Kabellengde	3,00 m
Farge	Sort
Dybde	4,4 cm
Høyde	179,1 cm
Vekt	6,93 kg
Bredde	5,6 cm

Input

Tillatt spenning	220...240 V
Maksimal linjestrøm	32 A
Inngangsstrøms grenser	32 A
Load capacity	7400 VA
Nettverksfrekvens	50/60 Hz
Plugg standard	IEC 60309 32 A 2P + E
Forsyningsspenning	200 V 208 V 230 V

Output

Antall strømuttak	36 IEC 60320 C13 6 IEC 60320 C19
-------------------	-------------------------------------

Overenstemmelse

Produktsertifikater	VDE
Standarder	IEC 60950

Miljømessig

Omgivelsestemperatur drift	-5...60 °C
Relativ fuktighet	5...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0,00...15240,00 m

Forpakkingsinformasjon

Forpakning 1 vekt	8,56 kg
Forpakning 1 høyde	200 cm
Forpakning 1 bredde	16,2 cm
Forpakning 1 lengde	10,7 cm
Antall enheter forpakning 3	48

Bærekraftig

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Blyfri	Ja
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Miljøinformasjon	 Produktmiljøprofil
Produktets livssyklus	 Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available

Garantiperiode

Garanti	2 years repair or replace
---------	---------------------------