



### Oversikt

|              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Presentasjon | APC Metered by Outlet with Switching Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and individual outlet power metering. Remote outlet level controls allow power on/off functionality for power recycling to reboot locked-up equipment and to avoid unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, and locking IEC receptacles. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager. |
| Leveringstid | Usually in Stock                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |

### Generelt

|                     |                                                                                                                   |
|---------------------|-------------------------------------------------------------------------------------------------------------------|
| Tilgjengelig utstyr | CAN port terminator<br>Installation guide<br>Rack mounting brackets<br>Safety guide<br>Serial configuration cable |
|---------------------|-------------------------------------------------------------------------------------------------------------------|

### Fysisk

|             |          |
|-------------|----------|
| Kabellengde | 3,00 m   |
| Farge       | Sort     |
| Dybde       | 5,1 cm   |
| Høyde       | 182,9 cm |
| Vekt        | 8,23 kg  |
| Bredde      | 5,6 cm   |

### Input

|                        |                         |
|------------------------|-------------------------|
| Tillatt spenning       | 220...240 V             |
| Maksimal linjestrøm    | 32 A                    |
| Inngangsstrøms grenser | 32 A                    |
| Load capacity          | 7400 VA                 |
| Nettverksfrekvens      | 50/60 Hz                |
| Plugg standard         | IEC 60309 32 A 2P + E   |
| Forsyningsspenning     | 200 V<br>208 V<br>230 V |

## Output

|                   |                                     |
|-------------------|-------------------------------------|
| Antall strømuttak | 21 IEC 60320 C13<br>3 IEC 60320 C19 |
|-------------------|-------------------------------------|

## Overenstemmelse

|                     |                                                               |
|---------------------|---------------------------------------------------------------|
| Produktsertifikater | VDE                                                           |
| Standarder          | EN 55022 klasse A<br>EN 55024<br>EN 61000-3-2<br>EN 61000-3-3 |

## Miljømessig

|                                  |                   |
|----------------------------------|-------------------|
| Omgivelsestemperatur drift       | -5...60 °C        |
| Relativ fuktighet                | 5...95 %          |
| Driftshøyde                      | 0...10000 ft      |
| Omgivelsestemperatur for lagring | -25...65 °C       |
| Storage Relative Humidity        | 5...95 %          |
| Storage altitude                 | 0,00...15240,00 m |

## Forpakkingsinformasjon

|                             |          |
|-----------------------------|----------|
| Forpakning 1 vekt           | 10,5 kg  |
| Forpakning 1 høyde          | 203,8 cm |
| Forpakning 1 bredde         | 16,2 cm  |
| Forpakning 1 lengde         | 11,8 cm  |
| Antall enheter forpakning 3 | 48       |

## Bærekraftig

|                                 |                                                                                                                            |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Produktets miljøstatus          | Green Premium miljømerket produkt                                                                                          |
| REACH-regelverk                 | <a href="#">REACH-erklæring</a>                                                                                            |
| EU RoHS-direktiv                | I samsvar <a href="#">EU RoHS-erklæring</a>                                                                                |
| Blyfri                          | Ja                                                                                                                         |
| Kvikksølvfri                    | Ja                                                                                                                         |
| Informasjon om RoHS-unntak      | <a href="#">Ja</a>                                                                                                         |
| Miljøinformasjon                | <a href="#">Produktmiljøprofil</a>                                                                                         |
| Produktets livssyklus           | <a href="#">Informasjon Om Levetidsslutt</a>                                                                               |
| WEEE                            | Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall. |
| Optimalisert energieffektivitet | Energieffektivt produkt                                                                                                    |
| Take-back                       | Take-back program available                                                                                                |

## Garantiperiode

|         |                           |
|---------|---------------------------|
| Garanti | 2 years repair or replace |
|---------|---------------------------|