



Oversikt

Presentasjon	APC Switched Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and active monitoring. Remote outlet level controls allow power on/off functionality for power recycling to remotely reboot equipment and restrict unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and low profile circuit breakers. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched Rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager.
Leveringstid	Usually in Stock

Generelt

Tilgjengelig utstyr	Installation guide Locking input power cord Rack mounting brackets Serial configuration cable Safety guide
---------------------	--

Fysisk

Kabellengde	3,00 m
Farge	Sort
Dybde	4,6 cm
Høyde	98,8 cm
Vekt	3,23 kg
Bredde	5,6 cm

Input

[In] merkestrøm	16 A
Tillatt spenning	220...240 V
Maksimal linjestrøm	16 A
Inngangsstrøms grenser	16 A
Load capacity	3700 VA
Nettverksfrekvens	50/60 Hz
Plugg standard	IEC 60309 16 A 2P + E
Forsyningsspenning	200 V 208 V 230 V

Output

Antall strømuttak	7 IEC 60320 C13 1 IEC 60320 C19
-------------------	------------------------------------

Overenstemmelse

Produktsertifikater	CUL listed PSE UL listet VCCI klasse A VDE
Standarder	EN 55022 klasse A EN 55024 EN 61000-3-2 EN 61000-3-3 FCC part 15 class A ICES-003

Miljømessig

Omgivelsestemperatur drift	-5...60 °C
Relativ fuktighet	5...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0,00...15240,00 m

Forpakkingsinformasjon

Forpakning 1 vekt	5,5 kg
Forpakning 1 høyde	112,5 cm
Forpakning 1 bredde	16,5 cm
Forpakning 1 lengde	11,4 cm

Bærekraftig

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Blyfri	Ja
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Miljøinformasjon	 Produktmiljøprofil
Produktets livssyklus	 Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available

Garantiperiode

Garanti	2 years repair or replace
---------	---------------------------