



Oversikt

Presentasjon	APC Metered Rack Power Distribution Units (PDUs) provide active metering to enable energy optimization and circuit protection. User-defined alarm thresholds mitigate risk with real-time local and remote alerts to warn of potential circuit overloads. Metered Rack PDUs provide power utilization data to allow Data Center Managers to make informed decisions on load balancing and right sizing IT environments to lower total cost of ownership. Metered Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and ultra low profile circuit breakers. Users can access and configure Metered Rack PDUs through secure Web, SNMP, or Telnet Interfaces which are complimented by APC Centralized Management platforms using InfraStruxure Central, Operations, Capacity, and Energy Efficiency.
Leveringstid	Usually in Stock

Generelt

Tilgjengelig utstyr	Installation guide Rack mounting brackets Serial configuration cable Safety guide
---------------------	--

Fysisk

Farge	Sort
Dybde	4,4 cm
Høyde	90,2 cm
Vekt	2,93 kg
Bredde	5,6 cm

Input

[In] merkestrøm	16 A
Tillatt spenning	100...240 V
Inngangsstrøms grenser	20 A
Load capacity	3300 VA
Nettverksfrekvens	50/60 Hz
Plugg standard	IEC 60320 C20
Forsyningsspenning	200 V 208 V 230 V

Output

Antall strømuttak	18 IEC 60320 C13 2 IEC 60320 C19
-------------------	-------------------------------------

Overenstemmelse

Produktsertifikater	METI Denan VDE
Standarder	CSA C22.2 No 60950 IEC 60950 UL 60950-1

Miljømessig

Omgivelsestemperatur drift	-5...60 °C
Relativ fuktighet	5...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0,00...15240,00 m

Forpakkingsinformasjon

Forpakning 1 vekt	4,2 kg
Forpakning 1 høyde	112,4 cm
Forpakning 1 bredde	16,2 cm
Forpakning 1 lengde	10,7 cm

Bærekraftig

Produkts miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Blyfri	Ja
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Miljøinformasjon	 Produktmiljøprofil
Produkts livssyklus	 Informasjon Om Levetidsslutt
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available

Garantiperiode

Garanti	2 years repair or replace
---------	---------------------------