



Oversikt

Leveringstid	Usually in Stock
--------------	------------------

Generelt

Inkludert utstyr	- Baying hardware - Key(S) - Keyed-alike doors and side panels - Leveling feet - Mounting hardware - Pre-installed casters - Side panels
------------------	--

Fysisk

Maks monteringsdybde	64,14 cm
Antall rack-enhet	42U
Minimum monteringsdybde	19,05 cm
Merking	18 gauge front door 19 gauge rear door 16 gauge post 14 gauge EIA mounting rail
Farge	Sort
Dybde	80 cm
Rack width	19"
Høyde	199,1 cm
Vekt	120,8 kg
Permanent tillatt belastning	1199,75 Kg statisk 599,65 kg dynamisk
Bredde	80 cm

Overenstemmelse

Standarder	- UL 60950-1 - UL 2416 - EIA-310E
------------	---

Forpakkingsinformasjon

Forpakning 1 vekt	128 kg
Forpakning 1 høyde	212 cm
Forpakning 1 bredde	85 cm
Forpakning 1 lengde	85 cm

Bærekraftig

EU RoHS-direktiv	Proaktivt i samsvar (Produktet inngår ikke i EUs RoHS direktivet)  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja

Garantiperiode

Garanti	5 year repair or replace
---------	--------------------------