DATASHEET - BPM-U-3S-400/7-W



3-component flush-mounted door frame with door, double-bit lock, IP54, HxW=760x400mm, white



BPM-U-3S-400/7-W Part no. 144238

Catalog No.

EL-Nummer (Norway)

2455263

Delivery program

| 71.3 | | |
|----------------------|----|---------------------|
| Mounting type | | Flush mounted |
| Features | | with door |
| Material | | Aluminium |
| Door interlock | | Double-ward lock |
| Installation site | | Moisture-proof |
| Degree of Protection | | IP54 |
| Surface finish | | With powder coating |
| Suitable for width | mm | 400 |
| Colour | | white (RAL 9016) |
| | | |

Technical data ETIM 7.0

Cabinet enclosures (EG000011) / Door/operating panel (switchgear cabinet) (EC000747)

Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Door (electrical cabinet) / Door/operating panel (enclosure) (ecl@ss10.0.1-27-18-22-04 [ACN614011])

| [ACN014011]) | | |
|---|----|----------------|
| Model | | Stop door |
| Version as glazed door | | No |
| Version as door for disconnecting switch interlocking | | No |
| Width | mm | 435 |
| Height | mm | 760 |
| Depth | mm | 85 |
| EMC-version | | No |
| Material | | Aluminium |
| Surface finishing | | Powder coating |
| Colour | | White |
| Degree of protection (IP) | | IP54 |
| Degree of protection (NEMA) | | |
| | | |