DATASHEET - BPM-U-3S-1000/17



3-component flush-mounting door frame with door, double-bit lock, IP54,



Part no. BPM-U-3S-1000/17

Catalog No. 111275

EL-Nummer 2459727

(Norway)

Delivery program

Features with door Material Aluminium Door interlock Double-ward lock Installation site Moisture-proof Degree of Protection IP54 Surface finish With powder coating Suitable for width mm 1000	- order / programm		
Material Aluminium Door interlock Double-ward lock Installation site Moisture-proof Degree of Protection IP54 Surface finish With powder coating Suitable for width mm 1000	Mounting type		Flush mounted
Door interlock Installation site Moisture-proof Degree of Protection IP54 Surface finish With powder coating Suitable for width Double-ward lock Moisture-proof With proof IP54 With powder coating	Features		with door
Installation site Degree of Protection Surface finish Suitable for width Moisture-proof IP54 With powder coating mm 1000	Material		Aluminium
Degree of Protection IP54 Surface finish With powder coating Suitable for width mm 1000	Door interlock		Double-ward lock
Surface finish With powder coating Suitable for width mm 1000	Installation site		Moisture-proof
Suitable for width mm 1000	Degree of Protection		IP54
	Surface finish		With powder coating
Colour light gray (RAL 7035)	Suitable for width	mm	1000
	Colour		light gray (RAL 7035)

Technical data ETIM 7.0

Cabinet enclosures (EG000011) / Door/operating panel (switchgear cabinet) (EC000747)

Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Door (electrical cabinet) / Door/operating panel (enclosure) (ecl@ss10.0.1-27-18-22-04 [ACN614011])

[AGN014011])		
Model		Stop door
Version as glazed door		No
Version as door for disconnecting switch interlocking		No
Width	mm	n 1035
Height	mm	n 1760
Depth	mm	n 85
EMC-version		No
Material		Aluminium
Surface finishing		Powder coating
Colour		Grey
Degree of protection (IP)		IP54
Degree of protection (NEMA)		