



Datablad / Stålrør 1250N

El-nr	Betegnelse	Innerdiam.	Ytterdiam.
12 269 01	Stålrør Tynnvegg 16 mm 1250N / 3m	14,0 mm	16 mm
12 269 07	Stålrør Tynnvegg 20 mm 1250N / 3m	18,0 mm	20 mm
12 269 08	Stålrør Tynnvegg 25 mm 1250N / 3m	22,6 mm	25 mm
12 269 09	Stålrør Tynnvegg 32 mm 1250N / 3m	29,6 mm	32 mm
12 269 10	Stålrør Tynnvegg 40 mm 1250N / 3m	37,6 mm	40 mm
12 269 11	Stålrør Tynnvegg 50 mm 1250N / 3m	47,6 mm	50 mm

Egenskaber	
Material	Mild steel rolled
Galvanized	Inside and outside hot dip galvanized acc. to EN ISO 1461 Ø – zinc coating 70 my / 500 g/m
Approval	VDE/ÖVE EN 61386-1 VDE/ÖVE EN 61386-21
Classification	4 = compressive strenght (1250N/5cm) 4 = impact strenght (2kg/300mm) 5 = min. temperature - 45° C 7 = max. temperature + 400° C
Korrosjonsklasse	C – 4