CENTER 380/382 REFRIGERANT LEAK DETECTOR

Features:

- Microprocessor Control with advanced digital signal processing.
- Multi color visual display.
- High-Low leak sensitivity selector.(380)
- High-Med-Low sensitivity selector.(382)
- Low battery indication.
- Semiconductor gas sensor.
- Detection of R-134a, R-410A, R-407C, R22... Freon gas.
- Carrying case included.
- 15.5" (40 CM) flexible stainless probe.
- Reference Leak source included.
- Ambient concentration reset.
- Long-life, DC brushless fan. (382)
- Variable intensity audible and visual alarms. (382)







REFRIGERANT LEAK DETECTOR

FEATURES

Air Sucking System for faster response and higher sensitivity. (382)

Refrigerant Leakage Detector is the perfect tool for maintaining the air-condition or a cooling system with compressor and Refrigerant.

This unit used newly developed semi-conductor sensor which is extremely sensitive to variety of general used Refrigerant.

Microprocessor Control with advanced digital signal processing.

SPECIFICATIONS

- Heated Semiconductor Gas Sensor.
- High-Low Leak Sensitivity Selector.(380)
- 3 Levels Of Sensitivity.(382)
- 7 LED Tri-colored Visual Leak Level Indicator.
- Variable Intensity Audible Alarm.
- Ambient Concentration Reset.
- 15.5"(40CM) Flexible Stainless Probe.
- Detection of R-134a, R-404A, R-410A, R-407C, R-22, R-502, R-600A...Refrigerants Gas.
- Sensitivity As Small 6gr/year(380); 3gr/year(382).
- Accordance With SAE J1627, CE Design.
- Low Battery Indication.
- Reference Leak Source Included.
- Hard Carrying case Included.
- Warm-up Time: 45 Seconds.(382)
- Operating Temperature: 0 to 40°C(32 to 104°F)
- Size: 21.7 x 6.6 x 5.6 cm
- Weight: 400g(with batteries)
- Power Source: 4 AA Size Alkaline Batteries.
- Battery Life: Appro. 40hrs(380)
- AC Adapter: @3.3V 0.5A(382)







* The specifications and other information in this catalogue are subject to change without prior notice.

