

CO₂
H₂S
Cl₂
NH₃
O₃
CO
O₂
CH₄
SO₂
CO₂
H₂S

TETRA:3

4 Gas Personal Monitor Oxygen, Toxic and Flammable Gases



TETRA:3

Proven to serve the needs of today's most arduous industrial environments.

Designed with the user in mind, the top mount display, full function data and event logs, audible, visual and vibrating alarms deliver top end performance in a small and lightweight package.

T3 features:

Robust

- Tough over-moulded contraction to resist shock and vibration
- Water and dust resistant to IP65 and IP67

Alarms

- 95dB Audible Alarm
- Piercingly bright red/blue visible alarm
- Vibrating alarm

Reliable

- Proven sensor technology and software operation
- 'At a glance' operating status
- Clear calibration due warning

Performance

- Li-ion battery with 14 hours operation
- True single button operation
- Easy to read back-lit display for gas readings and diagnostics

TETRA:3

Tetra 3 is an intuitive 4 gas personal monitor with a top mount display designed to withstand the harshest of industrial environments.

Gases and Ranges

Ranges and alarms may vary by country and application which can be configured as required. Each channel can have two instantaneous alarms. Toxic channels also have TWA alarms. Flammable gas calibration is available for methane, propane, butane, pentane, hydrogen and ethylene as standard.

* T3 is available in a safe area CO₂ version offering 0-5% carbon dioxide measurement. The CO₂ sensor replaces the flammable option and can be supplied with oxygen and toxic sensors.

Gas	Range	Typical Alarm (UK)
Flam	0-100% LEL	20%
O ₂	0-25%	19/23.5%
H ₂ S	0-100ppm	5ppm
CO	0-500ppm	30ppm
SO ₂	0-20ppm	1ppm
O ₃	0-1ppm	0.1ppm
NH ₃	0-100ppm	25ppm
*CO ₂	0-5%	0.5%

Gas Test Kit

The Gas Test Kit provides a simple and convenient means of carrying out either a pre-use (bump) test or a simultaneous four gas calibration (flam, O₂, H₂S, CO only).

Charging Options

The T3 can be supplied with:

- Single way drop in charger with UK, EU or US plug or in-line 110V/220V supply
- Single way drop in charger with options as above including PC interface
- 5 way multi-charger with universal power supply
- Vehicle adapter for in-vehicle charging
- **NEW** – Universal charger for vehicle, wall and desk mounting with a multi-region plug (supplied with EU/UK/US/Australian inserts) and status indication



Contact Crowcon for further information.



A HALMA COMPANY

UK: 2 Blacklands Way, Abingdon Business Park, Abingdon, OXON, OX14 1DY
+44 (0) 1235 557700 sales@crowcon.com

US: 21 Kenton Lands Road, Erlanger, Kentucky 41018-1845
+1 859 957 1039 salesusa@crowcon.com

NL: Vlambloem 129, 3068JG, Rotterdam
+31 10 421 1232 eu@crowcon.com

SG: Block 194 Pandan Loop, #06-20 Pantech Industrial Complex, Singapore, 128383
+65 6745 2936 sales@crowcon.com.sg

CN: Unit 316, Area 1, Tower B, Chuangxin Building, 12 Hongda North Road, Beijing Economic & Technological Development Area, Beijing, PRC 100176
+86 10 6787 0335 saleschina@crowcon.com

www.crowcon.com

PO1024 GB Issue 9 November 12

Specification

Weight	295g (10.4oz)
Dimensions	114 x 71 x 48mm (tapers to 20mm) 4.5 x 2.8 x 1.9 inches
Audible Alarms	95dB Multiple alarm sounds allow selection of distinctive tones for different alarm levels
Visible Alarms	Dual colour red/blue flashing LED in gas hazard
Vibrating Alarm	Internal vibrating alarm
Display	Graphic LCD with backlight, giving simultaneous display for all gas channels. Graphic symbols for battery (with proportional indication of remaining operation time), healthy operation or fault warning. Start up indication when calibration is due, overdue, or service required
Display Mode	Normal display for real time gas concentration levels. Display recall for Peak readings and TWA
Datalogging	Timed datalogging: 50 hours at 1-minute data rate (>12,000 data logs of 4 channels) Threshold logging (starts after adjustable preset level) Event logging: >5,000 events
Battery	Rechargeable Li-ion battery
Operating Time	Based on four gas unit with flammable sensor - A 5 hour charge from flat provides at least 10 hours of continuous use. A 12 hour charge provides at least 14 hours of continuous use
Sampling	Diffusion or hand aspirator
Operating Temp. Range	-20°C to +55°C (-4°F to +131°F) Toxic and Oxygen sensors are not rated for continuous operation at high temperatures. Consult Crowcon if operating temperatures are likely to exceed 40°C (104°F) for extended periods
Humidity	20-90% RH @ 40°C non-condensing
Ingress Protection	IP65 and IP67
Approval Codes Europe	ATEX II 2 G Ex ia d IIC T4 Gb (-20°C ≤ Ta ≤ +55°C) BASEEFA05ATEX0187
International	IECEx Ex ia d IIC T4 Gb (-20°C ≤ Ta ≤ +55°C) BAS05.0059
North America	CSA Class I Division 1 Groups A, B, C, D
Safety Standards Europe	EN60079-0, EN60079-11, EN60079-1, 94/9/EC
North America	CSA22.2, 152
Operation Standards	EN50270, EN50271, EN50104, EN45544, EN60079, IEC61508
PC Interface	RS232 connection from interface module in charger RS232/USB converter available
Calibration	Tetra 3 can be routinely calibrated using Portables PC software or Crowcon Checkbox IMH
Accessories	Tetra 3 is supplied with an integral alligator clip
Optional Accessories	Universal harness plate, shoulder strap, chest harness, aspirator assembly (flow plate, bulb and 2m/6ft tubing), fixed and telescopic sample probes, and an in-line water trap

Crowcon reserves the right to change the design or specification of this product without notice

Area reserved for distributor stamp

CROWCON
Detecting Gas Saving Lives