



STD-STD

Fiberadapter MM og SM



Materiale

Plast hus: PBT
Blå Ral 5015.
Metall hus: Nickel Plated Zinc Alloy
Støv hette: Vinyl

Sleeve Zirconia eller Phosphor Bronze
Zirconia (for SM): rød støv hette.
High Quality Phosphor Bronze
(for SM) : rød støv hette.
Standard Phosphor Bronze
(for MM) : Sort støv hette.

Typical Insertion Loss (dB)

AdapterType	SM at 1550 nm		MM at 1310 nm
	Zirconia Sleeve	High Quality Phosphor Bronze Sleeve	Standard Phosphor Bronze Sleeve
ST Duplex	0.08	0.12	0.10

- Strekkfasthet sveising (Plastik Adapter)> 100 N
- Innsetting tap variasjon under trekke kraft test <0,20 dB
- Innsetting tap variasjon etter 500 tilkoblinger <0,10 dB

min max temperatur:

Driftstemperatur: [°C] -25 +70

Lagringstemperatur: [°C] -40 +85

Molex art.nr	El.nr	Beskrivelse
AD12ZP1N	6910817	Adapter STD-STD SM, Zr sleeve skru montert Blå
AD12BP4N	6910813	Adapter STD-STD MM, Ph.Br. sleeve skru montert Metall