

Connector - with screwless terminals, for harsh applications





Product description	
BALS-Prd.-Nr	31421
EAN	4024941314213
Product category	Connector TE
Current	32A
Number of poles	4p
Arrangement of phases	3P+PE
Position of earth contact	11 h
Voltage	440 - 460V~

Product description	
Frequency	60Hz
Protection degree	IP67
Colour code	red RAL 3000
Colour of appliance	Hinged lid red RAL 3000, Enclosure red RAL 3000, Bayonet ring grey RAL 7035, Cable gland grey RAL 7035
Connection design	screwless spring terminals as cage clamp with Kontex-contact
Maximum conductor size	6,0 qmm
Cable entry	Cable gland
Height	198mm
Width	94mm
Depth	97mm
Material of enclosure	Polyamide
Contacts	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Logistics data	
Weight/pcs	0.347 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941314213
Length	97 mm
Width	94 mm

Logistics data	
Height	198 mm
Weight	0.348 kg
Volume	1,805.364 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941842976
Length	325 mm
Width	217 mm
Height	210 mm
Weight	3.676 kg
Volume	13,588.4 ccm

		Ampere Polzahl	16	16	16	32	32	32
			3	4	5	3	4	5
a ø			70,5	78,0	86,5	94,0	94,0	101,5
b			161,0	161,0	168,0	196,0	196,0	200,0
c			77,0	83,0	93,0	99,0	99,0	107,0
d ø			18,0	18,0	21,0	23,0	23,0	27,0
Leiter mm ² min			1	1	1	2,5	2,5	2,5
Leiter mm ² max			2,5	2,5	2,5	6	6	6

