

DATASHEET - CYLINDRICAL FUSE 14 X 51 25A GG 690V AC



Fuse-link, low voltage, 25 A, AC 690 V, 80 kA, 14 x 51 mm, gL/gG, IEC



Part no. **CYLINDRICAL FUSE 14 x 51 25A GG 690V AC**
Catalog No. **C14G25**

EL-Nummer **1600239**
(Norway)

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	25
Rated voltage			AC 690 V
Size			14 x 51 mm
Utilization category			gL/gG
Breaking Capacity		kA	80
usable for size/applications			for industrial applications for general purpose use
Standard/Approval			IEC
Shape			cylindrical
Standards/Regulations			IEC 60269-2

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013])			
Size			14x51 mm
Rated voltage		V	690 - 690
Rated voltage			Other
Voltage type			AC
Utilization category			gL/gG (cable protection/equipment protection)
Rated operating frequency		Hz	45 - 62
Nominal current		A	25
With striker			No
Release characteristic			Other
Breaking capacity		kA	80