



Distribution cabinet, HxWxD=1800x800x500mm, IP55

Part no. **XVTL-MP/BX/IC-8/5/18**
 Catalog No. **114570**

EL-Nummer **2459985**
 (Norway)

Delivery program

Product range			Control centres XVTL
Basic function			Combination enclosures
Single unit/Complete unit			Complete housing
Degree of Protection			IP55 (with door and flange)
Description			Fragment basic equipment Including open cable entries top, prepared for F3A flange
Material			Sheet steel 2 mm
Surface finish			Polyester powder coating Phosphated RAL 7035, light grey
Colour			light gray (RAL 7035)
Information about equipment supplied			including frame, sheet steel doors, back plate, bottom and top plate, mounting plate, lifting eyelets, cylinder lock and branding strip Including support frame for the IVS mounting units including insulating surround and mounted insulated support bracket Without side walls
Width		mm	800
Height		mm	1800
Depth		mm	500

Technical data

General

Standards			IEC/EN 60439-1 IEC/EN 60439-3 IEC/EN 62208
Protection class			1
			40 °C (intermittent maximum value) 35 °C (maximum value, 24 h average) -5 °C (minimum value)
Installation conditions			Indoor installation
Degree of Protection			IP55 (with door and flange)
Relative humidity			50% (at 40°C)
Power loss			
Max. admissible heat dissipation, ambient air temperature +35 °C		W	527
Weight		kg	101

Material characteristics

Material			Sheet steel 2 mm
Surface treatment			Painting, phosphated and polyester powder coating
Surface finish			Polyester powder coating Phosphated RAL 7035, light grey
Colour			light gray (RAL 7035)
Material characteristics			
Type Door			Outside-supported doors with hidden hinges Can be removed from 90°
door opening angle			120° (single mounting) 120° (combination mounting)
Door interlock			Folding handle with espagnolette lock Can be fitted with profile cylinder Three-point interlock

Material properties

Mechanical			
------------	--	--	--

Cable entry			Various covers allow cable entry from above and/or below
Electrical			
Rated insulation voltage	U _i	V	690
Rated operational voltage	U _e	V	415
Rated frequency	f	Hz	50 (AC)
Rated impulse withstand voltage	U _{imp}	kV	6
Rated operational current	I _e	A	2500
Overvoltage category/pollution degree			IV/3
Rated short-time withstand current (t=1s)	I _{cw}	kA	65
Rated peak withstand current	I _{pk}	kA	143
Max. admissible heat dissipation, ambient air temperature +35 °C		W	527
Earthings			Screw M10: 50 × 106 A ² s (base frame, main earthing) Taptite screw M6: 3.9 × 106 A ² s (enclosure side plate, back plate) M6 weld stud: 50 × 106 A ² s (door)

Design verification as per IEC/EN 61439

Technical data for design verification			
Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890			
Individual enclosure, free-standing	P _V	W	249
Starting enclosure, free-standing	P _V	W	236
Middle enclosure, free-standing	P _V	W	224
Individual enclosure for wall mounting	P _V	W	230
Starting enclosure for wall mounting	P _V	W	221
Middle enclosure for wall mounting	P _V	W	223
Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890			
Individual enclosure, free-standing	P _V	W	500
Starting enclosure, free-standing	P _V	W	473
Middle enclosure, free-standing	P _V	W	450
Individual enclosure for wall mounting	P _V	W	462
Starting enclosure for wall mounting	P _V	W	443
Middle enclosure for wall mounting	P _V	W	447
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Not applicable.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Not applicable.
10.2.4 Resistance to ultra-violet (UV) radiation			Not relevant to indoor installations.
10.2.5 Lifting			Met; assembled and secured as per the latest applicable instruction leaflet.
10.2.6 Mechanical impact			IK10
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES			IP55
10.4 Clearances and creepage distances			Is the panel builder's responsibility.
10.5 Protection against electric shock			< 0.1 Ω; meets the product standard's requirements.
10.6 Incorporation of switching devices and components			Is the panel builder's responsibility.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9 Insulation properties			
10.9.2 Power-frequency electric strength			U _i = 690 V AC
10.9.3 Impulse withstand voltage			6 kV
10.9.4 Testing of enclosures made of insulating material			Does not apply to metal enclosures.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating		Is the panel builder's responsibility.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility.
10.13 Mechanical function		Meets the product standard's requirements.

Technical data ETIM 7.0

Cabinet enclosures (EG000011) / Enclosure/switchgear cabinet (empty) (EC000261)			
Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Electrical cabinet (empty) / Electrical cabinet (ecl@ss10.0.1-27-18-01-01 [AGZ056016])			
Width	mm	800	
Height	mm	1800	
Depth	mm	500	
Material		Steel	
Material quality		Other	
Surface finishing		Powder coating	
Colour		Grey	
RAL-number		7035	
With mounting plate		Yes	
Mounting plate depth-adjustable		No	
Number of locks		1	
Floor installation possible		Yes	
Wall fastening possible		Yes	
Wall build in		No	
Pole fastening		No	
Tackable		Yes	
Number of doors		1	
Suitable for metrical mounting		Yes	
Suitable for outdoor set-up		No	
Pitched roof		No	
EMC-version		Yes	
With glazed door		No	
With ventilation door		No	
With backside door		No	
Impact strength		IK10	
Degree of protection (IP)		IP55	
Degree of protection (NEMA)			