



Distribution cabinet, HxWxD=1800x1000x300mm, IP55

Part no. XVTL-MP/BF-10/3/18
Catalog No. 114517

EL-Nummer 2459932
(Norway)

Design verification as per IEC/EN 61439

| | | | |
|---|----------------|---|--|
| Technical data for design verification | | | |
| Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 | | | |
| Individual enclosure, free-standing | P _V | W | 234 |
| Starting enclosure, free-standing | P _V | W | 228 |
| Middle enclosure, free-standing | P _V | W | 222 |
| Individual enclosure for wall mounting | P _V | W | 211 |
| Starting enclosure for wall mounting | P _V | W | 208 |
| Middle enclosure for wall mounting | P _V | W | 206 |
| Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890 | | | |
| Individual enclosure, free-standing | P _V | W | 470 |
| Starting enclosure, free-standing | P _V | W | 457 |
| Middle enclosure, free-standing | P _V | W | 445 |
| Individual enclosure for wall mounting | P _V | W | 423 |
| Starting enclosure for wall mounting | P _V | W | 417 |
| Middle enclosure for wall mounting | P _V | W | 413 |
| IEC/EN 61439 design verification | | | |
| 10.2 Strength of materials and parts | | | |
| 10.2.2 Corrosion resistance | | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | | Not applicable. |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects | | | Not applicable. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | | Not relevant to indoor installations. |
| 10.2.5 Lifting | | | Met; assembled and secured as per the latest applicable instruction leaflet. |
| 10.2.6 Mechanical impact | | | IK10 |
| 10.2.7 Inscriptions | | | Meets the product standard's requirements. |
| 10.3 Degree of protection of ASSEMBLIES | | | IP55 |
| 10.4 Clearances and creepage distances | | | Is the panel builder's responsibility. |
| 10.5 Protection against electric shock | | | < 0.1 Ω; meets the product standard's requirements. |
| 10.6 Incorporation of switching devices and components | | | Is the panel builder's responsibility. |
| 10.7 Internal electrical circuits and connections | | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | | Is the panel builder's responsibility. |
| 10.9 Insulation properties | | | |
| 10.9.2 Power-frequency electric strength | | | U _i = 690 V AC |
| 10.9.3 Impulse withstand voltage | | | 6 kV |
| 10.9.4 Testing of enclosures made of insulating material | | | Does not apply to metal enclosures. |
| 10.10 Temperature rise | | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | | Is the panel builder's responsibility. |
| 10.12 Electromagnetic compatibility | | | Is the panel builder's responsibility. |

| | | |
|---------------------------|--|--|
| 10.13 Mechanical function | | Meets the product standard's requirements. |
|---------------------------|--|--|

Technical data ETIM 7.0

| | | | |
|--|--|----|----------------|
| Cabinet enclosures (EG000011) / Enclosure/switchgear cabinet (empty) (EC000261) | | | |
| Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Electrical cabinet (empty) / Electrical cabinet (ecI@ss10.0.1-27-18-01-01 [AGZ056016]) | | | |
| Width | | mm | 1000 |
| Height | | mm | 1800 |
| Depth | | mm | 312 |
| Material | | | Steel |
| Material quality | | | Other |
| Surface finishing | | | Powder coating |
| Colour | | | Grey |
| RAL-number | | | 7035 |
| With mounting plate | | | No |
| Mounting plate depth-adjustable | | | Yes |
| Number of locks | | | 1 |
| Floor installation possible | | | Yes |
| Wall fastening possible | | | Yes |
| Wall build in | | | No |
| Pole fastening | | | No |
| Tackable | | | Yes |
| Number of doors | | | 2 |
| Suitable for metrical mounting | | | Yes |
| Suitable for outdoor set-up | | | No |
| Pitched roof | | | No |
| EMC-version | | | Yes |
| With glazed door | | | No |
| With ventilation door | | | No |
| With backside door | | | No |
| Impact strength | | | IK10 |
| Degree of protection (IP) | | | IP55 |
| Degree of protection (NEMA) | | | |