



Terminal, Insulation end connector blue, L=235mm

**Part no.** BPZ-IC/50-16/235-N  
**Catalog No.** 109261

**EL-Nummer** 1655613  
**(Norway)**

## Delivery program

|               |  |   |   |
|---------------|--|---|---|
| Mounting type |  |   | Floor standing distribution board<br>Surface mounted<br>Flush mounted |
| Length        |  | m | 235   |
| Colour        |  |   | Blue  |

## Technical data ETIM 7.0

|   |  |    |                |
|---|--|----|----------------|
| Energy distribution systems (EG000015) / Rail terminal bar (EC000275)   |  |    |                |
| Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Rail terminal bar clamp (ecI@ss10.0.1-27-40-06-03 [AC0369011]) |  |    |                |
| Number of poles   |  |    | 1              |
| Nominal current   |  | A  | 60             |
| Connection type   |  |    | Screwing       |
| Mounting method   |  |    | DIN-rail/screw |
| Number of connections total   |  |    | 2              |
| Number of connections < 6 mm <sup>2</sup>   |  |    | 0              |
| Number of connections 10 mm <sup>2</sup>  |  |    | 0              |
| Number of connections 16 mm <sup>2</sup>  |  |    | 1              |
| Number of connections 25 mm <sup>2</sup>  |  |    | 0              |
| Number of connections > 25 mm <sup>2</sup>  |  |    | 1              |
| Number of connections < AWG 6   |  |    | 0              |
| Number of connections AWG 6   |  |    | 0              |
| Number of connections AWG 4   |  |    | 0              |
| Number of connections AWG 2   |  |    | 0              |
| Number of connections AWG 4/0   |  |    | 0              |
| Number of connections 250 kcmil   |  |    | 0              |
| Number of connections > 250 kcmil   |  |    | 0              |
| Contact safe  |  |    | Yes            |
| Height  |  | mm | 30             |
| Width   |  | mm | 280            |
| Depth   |  | mm | 50             |