



3-component flush-mounting door frame with door, open air, double-bit lock, IP43, HxW=2060x1000mm

Part no. BPA-U-3S-1000/20
Catalog No. 111242

EL-Nummer (Norway) 2459694

Delivery program

| | | | |
|----------------------|--|----|-----------------------|
| Mounting type | | | Flush mounted |
| Features | | | with door |
| Material | | | Aluminium |
| Door interlock | | | Double-ward lock |
| Installation site | | | Outdoor |
| Degree of Protection | | | IP43 |
| Surface finish | | | With powder coating |
| Suitable for width | | mm | 1000 |
| Colour | | | light gray (RAL 7035) |

Technical data ETIM 7.0

| | | | |
|---|--|----|----------------|
| Cabinet enclosures (EG000011) / Door/operating panel (switchgear cabinet) (EC000747) | | | |
| Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Door (electrical cabinet) / Door/operating panel (enclosure) (ecl@ss10.0.1-27-18-22-04 [ACN614011]) | | | |
| Model | | | Stop door |
| Version as glazed door | | | No |
| Version as door for disconnecting switch interlocking | | | No |
| Width | | mm | 1035 |
| Height | | mm | 2060 |
| Depth | | mm | 85 |
| EMC-version | | | No |
| Material | | | Aluminium |
| Surface finishing | | | Powder coating |
| Colour | | | Grey |
| Degree of protection (IP) | | | IP43 |
| Degree of protection (NEMA) | | | |