



**3-component flush-mounting door frame with door, open air, double-bit lock, IP43, HxW=460x400mm**

**Part no. BPA-U-3S-400/4**  
**Catalog No. 111217**

**EL-Nummer 2459669**  
**(Norway)**

## Delivery program

|                      |  |    |                       |
|----------------------|--|----|-----------------------|
| Mounting type        |  |    | Flush mounted         |
| Features             |  |    | with door             |
| Material             |  |    | Aluminium             |
| Door interlock       |  |    | Double-ward lock      |
| Installation site    |  |    | Outdoor               |
| Degree of Protection |  |    | IP43                  |
| Surface finish       |  |    | With powder coating   |
| Suitable for width   |  | mm | 400                   |
| Colour               |  |    | light gray (RAL 7035) |

## Technical data ETIM 7.0

|                                                                                                                                                                                                         |  |    |                |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|----------------|
| Cabinet enclosures (EG000011) / Door/operating panel (switchgear cabinet) (EC000747)                                                                                                                    |  |    |                |
| Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Door (electrical cabinet) / Door/operating panel (enclosure) (ecl@ss10.0.1-27-18-22-04 [ACN614011]) |  |    |                |
| Model                                                                                                                                                                                                   |  |    | Stop door      |
| Version as glazed door                                                                                                                                                                                  |  |    | No             |
| Version as door for disconnecting switch interlocking                                                                                                                                                   |  |    | No             |
| Width                                                                                                                                                                                                   |  | mm | 435            |
| Height                                                                                                                                                                                                  |  | mm | 460            |
| Depth                                                                                                                                                                                                   |  | mm | 85             |
| EMC-version                                                                                                                                                                                             |  |    | No             |
| Material                                                                                                                                                                                                |  |    | Aluminium      |
| Surface finishing                                                                                                                                                                                       |  |    | Powder coating |
| Colour                                                                                                                                                                                                  |  |    | Grey           |
| Degree of protection (IP)                                                                                                                                                                               |  |    | IP43           |
| Degree of protection (NEMA)                                                                                                                                                                             |  |    |                |