


## DATASHEET - N43RS33



**N rail for fuse enclosure**



**Part no.** N43RS33  
**Catalog No.** 062989

**EL-Nummer (Norway)** 2502258

### Delivery program

|                                |  |                 |                                   |
|--------------------------------|--|-----------------|-----------------------------------|
|                                |  |                 |                                   |
| Product range                  |  |                 | Ci insulated enclosures           |
| Basic function                 |  |                 | Prepared enclosures               |
| Product function               |  |                 | Modular busbar system             |
| Accessories                    |  |                 | N bars                            |
| Single unit/Complete unit      |  |                 | Modular system                    |
| <b>Conductor cross-section</b> |  |                 |                                   |
| Solid                          |  | mm <sup>2</sup> | 2 x 2.5 - 35<br>4 x 1.5 - 16      |
| Stranded                       |  | mm <sup>2</sup> | 2 x 2.5 - 25<br>4 x 1.5 - 16      |
| For use with                   |  |                 | SE-RS-I43 (I44)<br>RS33/I43 (I44) |

### Technical data ETIM 7.0

|                                                                                                                                                                                                             |  |    |          |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|----------|
| Energy distribution systems (EG000015) / Rail terminal bar (EC000275)                                                                                                                                       |  |    |          |
| Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Rail terminal bar clamp (ecI@ss10.0.1-27-40-06-03 [AC0369011]) |  |    |          |
| Number of poles                                                                                                                                                                                             |  |    | 1        |
| Nominal current                                                                                                                                                                                             |  | A  | 63       |
| Connection type                                                                                                                                                                                             |  |    | Screwing |
| Mounting method                                                                                                                                                                                             |  |    | Screw    |
| Number of connections total                                                                                                                                                                                 |  |    | 6        |
| Number of connections < 6 mm <sup>2</sup>                                                                                                                                                                   |  |    | 0        |
| Number of connections 10 mm <sup>2</sup>                                                                                                                                                                    |  |    | 0        |
| Number of connections 16 mm <sup>2</sup>                                                                                                                                                                    |  |    | 4        |
| Number of connections 25 mm <sup>2</sup>                                                                                                                                                                    |  |    | 0        |
| Number of connections > 25 mm <sup>2</sup>                                                                                                                                                                  |  |    | 2        |
| Number of connections < AWG 6                                                                                                                                                                               |  |    | 0        |
| Number of connections AWG 6                                                                                                                                                                                 |  |    | 0        |
| Number of connections AWG 4                                                                                                                                                                                 |  |    | 0        |
| Number of connections AWG 2                                                                                                                                                                                 |  |    | 0        |
| Number of connections AWG 4/0                                                                                                                                                                               |  |    | 0        |
| Number of connections 250 kcmil                                                                                                                                                                             |  |    | 0        |
| Number of connections > 250 kcmil                                                                                                                                                                           |  |    | 0        |
| Contact safe                                                                                                                                                                                                |  |    | Yes      |
| Height                                                                                                                                                                                                      |  | mm | 0        |
| Width                                                                                                                                                                                                       |  | mm | 150      |
| Depth                                                                                                                                                                                                       |  | mm | 50       |

### Additional product information (links)

|                                                                             |                                                                                                                                                                                                                                                         |
|-----------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| allowInterrupt=1&RevisionSelectionMethod=LatestReleased&noSaveAs=0&Render=1 | <a href="http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&amp;model%20certification%20xEnergy%20Safety%20Ci">http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&amp;model certification xEnergy Safety Ci</a>                                   |
| allowInterrupt=1&RevisionSelectionMethod=LatestReleased&noSaveAs=0&Render=1 | <a href="http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&amp;Save%20time%20-%20we%20assist%20you%20with%20expert%20pre-assembly">http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&amp;Save time – we assist you with expert pre-assembly</a> |
| allowInterrupt=1&RevisionSelectionMethod=LatestReleased&noSaveAs=0&Render=1 | <a href="http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&amp;product%20information%20xEnergy%20Safety%20Ci">http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&amp;product information xEnergy Safety Ci</a>                                   |

|                                                                       |                                                                                                                                                                                                                                 |
|-----------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| tool for calculating the power loss for switching device combinations | <a href="http://www.eaton.eu/DE/Europe/Electrical/CustomerSupport/ConfigurationTools/TCTool/index.htm">http://www.eaton.eu/DE/Europe/Electrical/CustomerSupport/ConfigurationTools/TCTool/index.htm</a>                         |
| configurator - xEnergy family                                         | <a href="http://www.eaton.eu/DE/Europe/Electrical/CustomerSupport/ConfigurationTools/xEnergyMainSupport/index.htm">http://www.eaton.eu/DE/Europe/Electrical/CustomerSupport/ConfigurationTools/xEnergyMainSupport/index.htm</a> |